

# **C++/Tree Mapping User Manual**

Revision 2.2.0    August 2008

Copyright © 2005-2008 CODE SYNTHESIS TOOLS CC

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, version 1.2; with no Invariant Sections, no Front-Cover Texts and no Back-Cover Texts.

This document is available in the following formats: XHTML, PDF, and PostScript.



# Table of Contents

Preface . . . . .	1
About This Document . . . . .	1
More Information . . . . .	1
1 Introduction . . . . .	1
2 C++/Tree Mapping . . . . .	2
2.1 Preliminary Information . . . . .	2
2.1.1 Identifiers . . . . .	2
2.1.2 Character Type . . . . .	3
2.1.3 XML Schema Namespace . . . . .	3
2.1.4 Anonymous Types . . . . .	3
2.2 Error Handling . . . . .	3
2.2.1 <code>xml_schema::duplicate_id</code> . . . . .	4
2.3 Mapping for <code>import</code> and <code>include</code> . . . . .	5
2.3.1 <code>Import</code> . . . . .	5
2.3.2 Inclusion with Target Namespace . . . . .	5
2.3.3 Inclusion without Target Namespace . . . . .	5
2.4 Mapping for Namespaces . . . . .	6
2.5 Mapping for Built-in Data Types . . . . .	6
2.5.1 Inheritance from Built-in Data Types . . . . .	9
2.5.2 Mapping for <code>anyType</code> . . . . .	10
2.5.3 Mapping for <code>anySimpleType</code> . . . . .	11
2.5.4 Mapping for <code>QName</code> . . . . .	11
2.5.5 Mapping for <code>IDREF</code> . . . . .	12
2.5.6 Mapping for <code>base64Binary</code> and <code>hexBinary</code> . . . . .	14
2.5.7 Time Zone Representation . . . . .	17
2.5.8 Mapping for <code>date</code> . . . . .	18
2.5.9 Mapping for <code>dateTime</code> . . . . .	19
2.5.10 Mapping for <code>duration</code> . . . . .	20
2.5.11 Mapping for <code>gDay</code> . . . . .	22
2.5.12 Mapping for <code>gMonth</code> . . . . .	22
2.5.13 Mapping for <code>gMonthDay</code> . . . . .	23
2.5.14 Mapping for <code>gYear</code> . . . . .	24
2.5.15 Mapping for <code>gYearMonth</code> . . . . .	25
2.5.16 Mapping for <code>time</code> . . . . .	26
2.6 Mapping for Simple Types . . . . .	27
2.6.1 Mapping for Derivation by Restriction . . . . .	27
2.6.2 Mapping for Enumerations . . . . .	28
2.6.3 Mapping for Derivation by List . . . . .	29
2.6.4 Mapping for Derivation by Union . . . . .	30
2.7 Mapping for Complex Types . . . . .	31

2.7.1 Mapping for Derivation by Extension . . . . .	34
2.7.2 Mapping for Derivation by Restriction . . . . .	35
2.8 Mapping for Local Elements and Attributes . . . . .	35
2.8.1 Mapping for Members with the One Cardinality Class . . . . .	36
2.8.2 Mapping for Members with the Optional Cardinality Class . . . . .	37
2.8.3 Mapping for Members with the Sequence Cardinality Class . . . . .	41
2.9 Mapping for Global Elements . . . . .	43
2.10 Mapping for Global Attributes . . . . .	44
2.11 Mapping for <code>xsi:type</code> and Substitution Groups . . . . .	44
2.12 Mapping for <code>any</code> and <code>anyAttribute</code> . . . . .	45
2.12.1 Mapping for <code>any</code> with the One Cardinality Class . . . . .	47
2.12.2 Mapping for <code>any</code> with the Optional Cardinality Class . . . . .	48
2.12.3 Mapping for <code>any</code> with the Sequence Cardinality Class . . . . .	52
2.12.4 Mapping for <code>anyAttribute</code> . . . . .	57
2.13 Mapping for Mixed Content Models . . . . .	62
3 Parsing . . . . .	62
3.1 Initializing the Xerces-C++ Runtime . . . . .	64
3.2 Flags and Properties . . . . .	65
3.3 Error Handling . . . . .	66
3.3.1 <code>xml_schema::parsing</code> . . . . .	67
3.3.2 <code>xml_schema::expected_element</code> . . . . .	69
3.3.3 <code>xml_schema::unexpected_element</code> . . . . .	69
3.3.4 <code>xml_schema::expected_attribute</code> . . . . .	70
3.3.5 <code>xml_schema::unexpected_enumerator</code> . . . . .	70
3.3.6 <code>xml_schema::expected_text_content</code> . . . . .	71
3.3.7 <code>xml_schema::no_type_info</code> . . . . .	71
3.3.8 <code>xml_schema::not_derived</code> . . . . .	71
3.3.9 <code>xml_schema::no_prefix_mapping</code> . . . . .	72
3.4 Reading from a Local File or URI . . . . .	72
3.5 Reading from <code>std::istream</code> . . . . .	73
3.6 Reading from <code>xercesc::InputSource</code> . . . . .	73
3.7 Reading from DOM . . . . .	73
4 Serialization . . . . .	74
4.1 Initializing the Xerces-C++ Runtime . . . . .	76
4.2 Namespace Infomap and Character Encoding . . . . .	76
4.3 Flags . . . . .	78
4.4 Error Handling . . . . .	79
4.4.1 <code>xml_schema::serialization</code> . . . . .	79
4.4.2 <code>xml_schema::unexpected_element</code> . . . . .	80
4.4.3 <code>xml_schema::no_type_info</code> . . . . .	80
4.5 Serializing to <code>std::ostream</code> . . . . .	80
4.6 Serializing to <code>xercesc::XMLFormatTarget</code> . . . . .	81
4.7 Serializing to DOM . . . . .	82

5 Additional Functionality . . . . .	82
5.1 DOM Association . . . . .	83
5.2 Binary Serialization . . . . .	85
Appendix A — Default and Fixed Values . . . . .	86



# Preface

## About This Document

This document describes the mapping of W3C XML Schema to the C++ programming language as implemented by CodeSynthesis XSD - an XML Schema to C++ data binding compiler. The mapping represents information stored in XML instance documents as a statically-typed, tree-like in-memory data structure and is called C++/Tree.

### Revision 2.2.0

This revision of the manual describes the C++/Tree mapping as implemented by CodeSynthesis XSD version 3.2.0.

This document is available in the following formats: XHTML, PDF, and PostScript.

## More Information

Beyond this manual, you may also find the following sources of information useful:

- C++/Tree Mapping Getting Started Guide
- C++/Tree Mapping Customization Guide
- C++/Tree Mapping and Berkeley DB XML Integration Guide
- C++/Tree Mapping Frequently Asked Questions (FAQ)
- XSD Compiler Command Line Manual
- The `examples/cxx/tree/` directory in the XSD distribution contains a collection of examples and a README file with an overview of each example.
- The README file in the XSD distribution explains how to compile the examples on various platforms.
- The xsd-users mailing list is a place to ask questions. Furthermore the archives may already have answers to some of your questions.

## 1 Introduction

C++/Tree is a W3C XML Schema to C++ mapping that represents the data stored in XML as a statically-typed, vocabulary-specific object model. Based on a formal description of an XML vocabulary (schema), the C++/Tree mapping produces a tree-like data structure suitable for in-memory processing as well as XML parsing and serialization code.

A typical application that processes XML documents usually performs the following three steps: it first reads (parsing) an XML instance document to an object model, it then performs some useful computations on that model which may involve modification of the model, and finally it may

write (serialize) the modified object model back to XML.

The C++/Tree mapping consists of C++ types that represent the given vocabulary (Chapter 2, "C++/Tree Mapping"), a set of parsing functions that convert XML documents to a tree-like in-memory data structure (Chapter 3, "Parsing"), and a set of serialization functions that convert the object model back to XML (Chapter 4, "Serialization"). Furthermore, the mapping provides a number of additional features, such as DOM association and binary serialization, that can be useful in some applications (Chapter 5, "Additional Functionality").

## 2 C++/Tree Mapping

### 2.1 Preliminary Information

#### 2.1.1 Identifiers

XML Schema names may happen to be reserved C++ keywords or contain characters that are illegal in C++ identifiers. To avoid C++ compilation problems, such names are changed (escaped) when mapped to C++. If an XML Schema name is a C++ keyword, the "\_" suffix is added to it. All character of an XML Schema name that are not allowed in C++ identifiers are replaced with "\_".

For example, XML Schema name `try` will be mapped to C++ identifier `try_`. Similarly, XML Schema name `strange.name` will be mapped to C++ identifier `strange_name`.

Furthermore, conflicts between type names and function names in the same scope are resolved using name escaping. Such conflicts include both a global element (which is mapped to a set of parsing and/or serialization functions, see Section 2.9, "Mapping for Global Elements") and a global type sharing the same name as well as a local element or attribute inside a type having the same name as the type itself.

For example, if we had a global type `catalog` and a global element with the same name then the type would be mapped to a C++ class with name `catalog` while the parsing functions corresponding to the global element would have their names escaped as `catalog_`.

By default the mapping uses the so-called K&R (Kernighan and Ritchie) identifier naming convention which is also used throughout this manual. In this convention both type and function names are in lower case and words are separated by underscores. If your application code or schemas use a different notation, you may want to change the naming convention used by the mapping for consistency. The compiler supports a set of widely-used naming conventions that you can select with the `--type-naming` and `--function-naming` options. You can also further refine one of the predefined conventions or create a completely custom naming scheme by using the `--*-regex` options. For more detailed information on these options refer to the NAMING CONVENTION section in the XSD Compiler Command Line Manual.

### 2.1.2 Character Type

The code that implements the mapping, depending on the `--char-type` option, is generated using either `char` or `wchar_t` as the character type. In this document code samples use symbol `C` to refer to the character type you have selected when translating your schemas, for example `std::basic_string<C>`.

### 2.1.3 XML Schema Namespace

The mapping relies on some predefined types, classes, and functions that are logically defined in the XML Schema namespace reserved for the XML Schema language (<http://www.w3.org/2001/XMLSchema>). By default, this namespace is mapped to C++ namespace `xml_schema`. It is automatically accessible from a C++ compilation unit that includes a header file generated from an XML Schema definition.

Note that, if desired, the default mapping of this namespace can be changed as described in Section 2.4, "Mapping for Namespaces".

### 2.1.4 Anonymous Types

For the purpose of code generation, anonymous types defined in XML Schema are automatically assigned names that are derived from enclosing attributes and elements. Otherwise, such types follows standard mapping rules for simple and complex type definitions (see Section 2.6, "Mapping for Simple Types" and Section 2.7, "Mapping for Complex Types"). For example, in the following schema fragment:

```
<element name="object">
  <complexType>
    ...
  </complexType>
</element>
```

The anonymous type defined inside element `object` will be given name `object`. The compiler has a number of options that control the process of anonymous type naming. For more information refer to the XSD Compiler Command Line Manual.

## 2.2 Error Handling

The mapping uses the C++ exception handling mechanism as a primary way of reporting error conditions. All exceptions that are specified in this mapping derive from `xml_schema::exception` which itself is derived from `std::exception`:

```

struct exception: virtual std::exception
{
    friend
    std::basic_ostream<C>&
    operator<< (std::basic_ostream<C>& os, const exception& e)
    {
        e.print (os);
        return os;
    }

protected:
    virtual void
    print (std::basic_ostream<C>&) const = 0;
};

```

The exception hierarchy supports "virtual" `operator<<` which allows you to obtain diagnostics corresponding to the thrown exception using the base exception interface. For example:

```

try
{
    ...
}
catch (const xml_schema::exception& e)
{
    cerr << e << endl;
}

```

The following sub-sections describe exceptions thrown by the types that constitute the object model. Section 3.3, "Error Handling" of Chapter 3, "Parsing" describes exceptions and error handling mechanisms specific to the parsing functions. Section 4.4, "Error Handling" of Chapter 4, "Serialization" describes exceptions and error handling mechanisms specific to the serialization functions.

## 2.2.1 xml\_schema::duplicate\_id

```

struct duplicate_id: virtual exception
{
    duplicate_id (const std::basic_string<C>& id);

    const std::basic_string<C>&
    id () const;

    virtual const char*
    what () const throw ();
};

```

The `xml_schema::duplicate_id` is thrown when a conflicting instance of `xml_schema::id` (see Section 2.5, "Mapping for Built-in Data Types") is added to a tree. The offending ID value can be obtained using the `id` function.

## 2.3 Mapping for import and include

### 2.3.1 Import

The XML Schema `import` element is mapped to the C++ Preprocessor `#include` directive. The value of the `schemaLocation` attribute is used to derive the name of the header file that appears in the `#include` directive. For instance:

```
<import namespace="http://www.codesynthesis.com/test"
        schemaLocation="test.xsd"/>
```

is mapped to:

```
#include "test.hxx"
```

Note that you will need to compile imported schemas separately in order to produce corresponding header files.

### 2.3.2 Inclusion with Target Namespace

The XML Schema `include` element which refers to a schema with a target namespace or appears in a schema without a target namespace follows the same mapping rules as the `import` element, see Section 2.3.1, "Import".

### 2.3.3 Inclusion without Target Namespace

For the XML Schema `include` element which refers to a schema without a target namespace and appears in a schema with a target namespace (such inclusion sometimes called "chameleon inclusion"), declarations and definitions from the included schema are generated in-line in the namespace of the including schema as if they were declared and defined there verbatim. For example, consider the following two schemas:

```
<-- common.xsd -->
<schema>
  <complexType name="type">
    ...
  </complexType>
</schema>

<-- test.xsd -->
<schema targetNamespace="http://www.codesynthesis.com/test">
  <include schemaLocation="common.xsd"/>
</schema>
```

The fragment of interest from the generated header file for `text.xsd` would look like this:

```
// test.hxx
namespace test
{
    class type
    {
        ...
    };
}
```

## 2.4 Mapping for Namespaces

An XML Schema namespace is mapped to one or more nested C++ namespaces. XML Schema namespaces are identified by URIs. By default, a namespace URI is mapped to a sequence of C++ namespace names by removing the protocol and host parts and splitting the rest into a sequence of names with `'/'` as the name separator. For instance:

```
<schema targetNamespace="http://www.codesynthesis.com/system/test">
    ...
</schema>
```

is mapped to:

```
namespace system
{
    namespace test
    {
        ...
    }
}
```

The default mapping of namespace URIs to C++ namespace names can be altered using the `--namespace-map` and `--namespace-regex` options. See the XSD Compiler Command Line Manual for more information.

## 2.5 Mapping for Built-in Data Types

The mapping of XML Schema built-in data types to C++ types is summarized in the table below.

XML Schema type	Alias in the <code>xml_schema</code> namespace	C++ type
<b>anyType and anySimpleType types</b>		
<code>anyType</code>	<code>type</code>	Section 2.5.2, "Mapping for anyType"

anySimpleType	simple_type	Section 2.5.3, "Mapping for anySimple-Type"
<b>fixed-length integral types</b>		
byte	byte	signed char
unsignedByte	unsigned_byte	unsigned char
short	short_	short
unsignedShort	unsigned_short	unsigned short
int	int_	int
unsignedInt	unsigned_int	unsigned int
long	long_	long long
unsignedLong	unsigned_long	unsigned long long
<b>arbitrary-length integral types</b>		
integer	integer	long long
nonPositiveInteger	non_positive_integer	long long
nonNegativeInteger	non_negative_integer	long long
positiveInteger	positive_integer	long long
negativeInteger	negative_integer	long long
<b>boolean types</b>		
boolean	boolean	bool
<b>fixed-precision floating-point types</b>		
float	float_	float
double	double_	double
<b>arbitrary-precision floating-point types</b>		
decimal	decimal	double
<b>string types</b>		
string	string	type derived from std::basic_string
normalizedString	normalized_string	type derived from string
token	token	type derived from normalized_string
Name	name	type derived from token

NMTOKEN	nmtoken	type derived from token
NMTOKENS	nmtokens	type derived from sequence<nmtoken>
NCName	ncname	type derived from name
language	language	type derived from token
qualified name		
QName	qname	Section 2.5.4, "Mapping for QName"
ID/IDREF types		
ID	id	type derived from ncname
IDREF	idref	Section 2.5.5, "Mapping for IDREF"
IDREFS	idrefs	type derived from sequence<idref>
URI types		
anyURI	uri	type derived from std::basic_string
binary types		
base64Binary	base64_binary	Section 2.5.6, "Mapping for base64Binary and hexBinary"
hexBinary	hex_binary	
date/time types		
date	date	Section 2.5.8, "Mapping for date"
dateTime	date_time	Section 2.5.9, "Mapping for dateTime"
duration	duration	Section 2.5.10, "Mapping for duration"
gDay	gday	Section 2.5.11, "Mapping for gDay"
gMonth	gmonth	Section 2.5.12, "Mapping for gMonth"
gMonthDay	gmonth_day	Section 2.5.13, "Mapping for gMonth- Day"
gYear	gyear	Section 2.5.14, "Mapping for gYear"
gYearMonth	gyear_month	Section 2.5.15, "Mapping for gYear- Month"
time	time	Section 2.5.16, "Mapping for time"
entity types		
ENTITY	entity	type derived from name

ENTITIES	entities	type derived from <code>sequence&lt;entity&gt;</code>
----------	----------	---

All XML Schema built-in types are mapped to C++ classes that are derived from the `xml_schema::simple_type` class except where the mapping is to a fundamental C++ type.

The `sequence` class template is defined in an implementation-specific namespace. It conforms to the `sequence` interface as defined by the ISO/ANSI Standard for C++ (ISO/IEC 14882:1998, Section 23.1.1, "Sequences"). Practically, this means that you can treat such a sequence as if it was `std::vector`. One notable extension to the standard interface that is available only for sequences of non-fundamental C++ types is the addition of the overloaded `push_back` and `insert` member functions which instead of the constant reference to the element type accept automatic pointer to the element type. These functions assume ownership of the pointed to object and resets the passed automatic pointer.

## 2.5.1 Inheritance from Built-in Data Types

In cases where the mapping calls for an inheritance from a built-in type which is mapped to a fundamental C++ type, a proxy type is used instead of the fundamental C++ type (C++ does not allow inheritance from fundamental types). For instance:

```
<simpleType name="my_int">
  <restriction base="int"/>
</simpleType>
```

is mapped to:

```
class my_int: public fundamental_base<int>
{
    ...
};
```

The `fundamental_base` class template provides a close emulation (though not exact) of a fundamental C++ type. It is defined in an implementation-specific namespace and has the following interface:

```
template <typename X>
class fundamental_base: public simple_type
{
public:
    fundamental_base ();
    fundamental_base (X)
    fundamental_base (const fundamental_base&)

public:
    fundamental_base&
    operator= (const X&);
```

```

public:
    operator const X & () const;
    operator X& ();

    template <typename Y>
    operator Y () const;

    template <typename Y>
    operator Y ();
};

```

## 2.5.2 Mapping for anyType

The XML Schema anyType built-in data type is mapped to the `xml_schema::type` C++ class:

```

class type
{
public:
    virtual
    ~type ();

public:
    type ();
    type (const type&);

public:
    type&
    operator= (const type&);

public:
    virtual type*
    _clone () const;

    // DOM association.
    //
public:
    const xercesc::DOMNode*
    _node () const;

    xercesc::DOMNode*
    _node ();
};

```

For more information about DOM association refer to Section 5.1, "DOM Association".

## 2.5.3 Mapping for anySimpleType

The XML Schema anySimpleType built-in data type is mapped to the `xml_schema::simple_type` C++ class:

```
class simple_type: public type
{
public:
    simple_type ();
    simple_type (const simple_type&);

public:
    simple_type&
    operator= (const simple_type&);

public:
    virtual simple_type*
    _clone () const;
};
```

## 2.5.4 Mapping for QName

The XML Schema QName built-in data type is mapped to the `xml_schema::qname` C++ class:

```
class qname: public simple_type
{
public:
    qname (const nname&);
    qname (const uri&, const nname&);
    qname (const qname&);

public:
    qname&
    operator= (const qname&);

public:
    virtual qname*
    _clone () const;

public:
    bool
    qualified () const;

    const uri&
    namespace_ () const;
```

```

    const ncname&
    name () const;
};

```

The qualified accessor function can be used to determine if the name is qualified.

## 2.5.5 Mapping for IDREF

The XML Schema IDREF built-in data type is mapped to the `xml_schema::idref` C++ class. This class implements the smart pointer C++ idiom:

```

class idref: public ncname
{
public:
    idref (const C* s);
    idref (const C* s, std::size_t n);
    idref (std::size_t n, C c);
    idref (const std::basic_string<C>&);
    idref (const std::basic_string<C>&,
          std::size_t pos,
          std::size_t n = npos);

public:
    idref (const idref&);

public:
    virtual idref*
    _clone () const;

public:
    idref&
    operator= (C c);

    idref&
    operator= (const C* s);

    idref&
    operator= (const std::basic_string<C>&)

    idref&
    operator= (const idref&);

public:
    const type*
    operator-> () const;

    type*
    operator-> ();

```

```

const type&
operator* () const;

type&
operator* ();

const type*
get () const;

type*
get ();

// Conversion to bool.
//
public:
    typedef void (idref::*bool_convertible)();
    operator bool_convertible () const;
};

```

The object, `idref` instance refers to, is the immediate container of the matching `id` instance. For example, with the following instance document and schema:

```

<!-- test.xml -->
<root>
  <object id="obj-1" text="hello"/>
  <reference>obj-1</reference>
</root>

<!-- test.xsd -->
<schema>
  <complexType name="object_type">
    <attribute name="id" type="ID"/>
    <attribute name="text" type="string"/>
  </complexType>

  <complexType name="root_type">
    <sequence>
      <element name="object" type="object_type"/>
      <element name="reference" type="IDREF"/>
    </sequence>
  </complexType>

  <element name="root" type="root_type"/>
</schema>

```

The `ref` instance in the code below will refer to an object of type `object_type`:

```

root_type& root = ...;
xml_schema::idref& ref (root.reference ());
object_type& obj (dynamic_cast<object_type&> (*ref));
cout << obj.text () << endl;

```

The smart pointer interface of the `idref` class always returns a pointer or reference to `xml_schema::type`. This means that you will need to manually cast such pointer or reference to its real (dynamic) type before you can use it (unless all you need is the base interface provided by `xml_schema::type`). As a special extension to the XML Schema language, the mapping supports static typing of `idref` references by employing the `refType` extension attribute. The following example illustrates this mechanism:

```
<!-- test.xsd -->
<schema
  xmlns:xse="http://www.codesynthesis.com/xmlns/xml-schema-extension">

  ...

  <element name="reference" type="IDREF" xse:refType="object_type"/>

  ...

</schema>
```

With this modification we do not need to do manual casting anymore:

```
root_type& root = ...;
root_type::reference_type& ref (root.reference ());
object_type& obj (*ref);
cout << ref->text () << endl;
```

## 2.5.6 Mapping for base64Binary and hexBinary

The XML Schema `base64Binary` and `hexBinary` built-in data types are mapped to the `xml_schema::base64_binary` and `xml_schema::hex_binary` C++ classes, respectively. The `base64_binary` and `hex_binary` classes support a simple buffer abstraction by inheriting from the `xml_schema::buffer` class:

```
class bounds: public virtual exception
{
public:
  virtual const char*
  what () const throw ();
};

class buffer
{
public:
  typedef std::size_t size_t;

public:
  buffer (size_t size = 0);
  buffer (size_t size, size_t capacity);
  buffer (const void* data, size_t size);
```

```

buffer (const void* data, size_t size, size_t capacity);
buffer (void* data,
        size_t size,
        size_t capacity,
        bool assume_ownership);

public:
    buffer (const buffer&);

    buffer&
    operator= (const buffer&);

    void
    swap (buffer&);

public:
    size_t
    capacity () const;

    bool
    capacity (size_t);

public:
    size_t
    size () const;

    bool
    size (size_t);

public:
    const char*
    data () const;

    char*
    data ();

    const char*
    begin () const;

    char*
    begin ();

    const char*
    end () const;

    char*
    end ();
};

```

If the `assume_ownership` argument to the constructor is `true`, the instance assumes ownership of the memory block pointed to by the `data` argument and will eventually release it by calling operator `delete`. The `capacity` and `size` modifier functions return `true` if the underlying buffer has moved.

The bounds exception is thrown if the constructor arguments violate the `(size <= capacity)` constraint.

The `base64_binary` and `hex_binary` classes support the `buffer` interface and perform automatic decoding/encoding from/to the Base64 and Hex formats, respectively:

```
class base64_binary: public simple_type, public buffer
{
public:
    base64_binary (size_t size = 0);
    base64_binary (size_t size, size_t capacity);
    base64_binary (const void* data, size_t size);
    base64_binary (const void* data, size_t size, size_t capacity);
    base64_binary (void* data,
                  size_t size,
                  size_t capacity,
                  bool assume_ownership);

public:
    base64_binary (const base64_binary&);

    base64_binary&
    operator= (const base64_binary&);

    virtual base64_binary*
    _clone () const;

public:
    std::basic_string<C>
    encode () const;
};

class hex_binary: public simple_type, public buffer
{
public:
    hex_binary (size_t size = 0);
    hex_binary (size_t size, size_t capacity);
    hex_binary (const void* data, size_t size);
    hex_binary (const void* data, size_t size, size_t capacity);
    hex_binary (void* data,
                size_t size,
                size_t capacity,
                bool assume_ownership);

public:
```

```

hex_binary (const hex_binary&);

hex_binary&
operator= (const hex_binary&);

virtual hex_binary*
_clone () const;

public:
    std::basic_string<C>
    encode () const;
};

```

## 2.5.7 Time Zone Representation

The date, dateTime, gDay, gMonth, gMonthDay, gYear, gYearMonth, and time XML Schema built-in types all include an optional time zone component. The following `xml_schema::time_zone` base class is used to represent this information:

```

class time_zone
{
public:
    time_zone ();
    time_zone (short hours, short minutes);

    bool
    zone_present () const;

    void
    zone_reset ();

    short
    zone_hours () const;

    void
    zone_hours (short);

    short
    zone_minutes () const;

    void
    zone_minutes (short);
};

bool
operator== (const time_zone&, const time_zone&);

bool
operator!= (const time_zone&, const time_zone&);

```

The `zone_present()` accessor function returns `true` if the time zone is specified. The `zone_reset()` modifier function resets the time zone object to the *not specified* state. If the time zone offset is negative then both hours and minutes components are represented as negative integers.

## 2.5.8 Mapping for date

The XML Schema `date` built-in data type is mapped to the `xml_schema::date` C++ class which represents year, day, and month with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```
class date: public simple_type, public time_zone
{
public:
    date (int year, unsigned short month, unsigned short day);
    date (int year, unsigned short month, unsigned short day,
          short zone_hours, short zone_minutes);

public:
    date (const date&);

    date&
    operator= (const date&);

    virtual date*
    _clone () const;

public:
    int
    year () const;

    void
    year (int);

    unsigned short
    month () const;

    void
    month (unsigned short);

    unsigned short
    day () const;

    void
    day (unsigned short);
};

bool
```

```
operator== (const date&, const date&);
```

```
bool
```

```
operator!= (const date&, const date&);
```

## 2.5.9 Mapping for dateTime

The XML Schema dateTime built-in data type is mapped to the `xml_schema::date_time` C++ class which represents year, month, day, hours, minutes, and seconds with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```
class date_time: public simple_type, public time_zone
{
public:
    date_time (int year, unsigned short month, unsigned short day,
               unsigned short hours, unsigned short minutes,
               double seconds);

    date_time (int year, unsigned short month, unsigned short day,
               unsigned short hours, unsigned short minutes,
               double seconds, short zone_hours, short zone_minutes);
public:
    date_time (const date_time&);

    date_time&
    operator= (const date_time&);

    virtual date_time*
    _clone () const;

public:
    int
    year () const;

    void
    year (int);

    unsigned short
    month () const;

    void
    month (unsigned short);

    unsigned short
    day () const;

    void
    day (unsigned short);
```

```

    unsigned short
    hours () const;

    void
    hours (unsigned short);

    unsigned short
    minutes () const;

    void
    minutes (unsigned short);

    double
    seconds () const;

    void
    seconds (double);
};

bool
operator== (const date_time&, const date_time&);

bool
operator!= (const date_time&, const date_time&);

```

## 2.5.10 Mapping for duration

The XML Schema duration built-in data type is mapped to the `xml_schema::duration` C++ class which represents a potentially negative duration in the form of years, months, days, hours, minutes, and seconds. Its interface is presented below.

```

class duration: public simple_type
{
public:
    duration (bool negative,
              unsigned int years, unsigned int months, unsigned int days,
              unsigned int hours, unsigned int minutes, double seconds);
public:
    duration (const duration&);

    duration&
    operator= (const duration&);

    virtual duration*
    _clone () const;

public:
    bool
    negative () const;

```

```

void
negative (bool);

unsigned int
years () const;

void
years (unsigned int);

unsigned int
months () const;

void
months (unsigned int);

unsigned int
days () const;

void
days (unsigned int);

unsigned int
hours () const;

void
hours (unsigned int);

unsigned int
minutes () const;

void
minutes (unsigned int);

double
seconds () const;

void
seconds (double);
};

bool
operator== (const duration&, const duration&);

bool
operator!= (const duration&, const duration&);

```

## 2.5.11 Mapping for gDay

The XML Schema gDay built-in data type is mapped to the `xml_schema::gday` C++ class which represents a day of the month with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```
class gday: public simple_type, public time_zone
{
public:
    explicit
    gday (unsigned short day);
    gday (unsigned short day, short zone_hours, short zone_minutes);

public:
    gday (const gday&);

    gday&
    operator= (const gday&);

    virtual gday*
    _clone () const;

public:
    unsigned short
    day () const;

    void
    day (unsigned short);
};

bool
operator== (const gday&, const gday&);

bool
operator!= (const gday&, const gday&);
```

## 2.5.12 Mapping for gMonth

The XML Schema gMonth built-in data type is mapped to the `xml_schema::gmonth` C++ class which represents a month of the year with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```
class gmonth: public simple_type, public time_zone
{
public:
    explicit
```

```

gmonth (unsigned short month);
gmonth (unsigned short month,
        short zone_hours, short zone_minutes);

public:
    gmonth (const gmonth&);

    gmonth&
    operator= (const gmonth&);

    virtual gmonth*
    _clone () const;

public:
    unsigned short
    month () const;

    void
    month (unsigned short);
};

bool
operator== (const gmonth&, const gmonth&);

bool
operator!= (const gmonth&, const gmonth&);

```

## 2.5.13 Mapping for gMonthDay

The XML Schema gMonthDay built-in data type is mapped to the `xml_schema::gmonth_day` C++ class which represents day and month of the year with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```

class gmonth_day: public simple_type, public time_zone
{
public:
    gmonth_day (unsigned short month, unsigned short day);
    gmonth_day (unsigned short month, unsigned short day,
                short zone_hours, short zone_minutes);

public:
    gmonth_day (const gmonth_day&);

    gmonth_day&
    operator= (const gmonth_day&);

    virtual gmonth_day*
    _clone () const;

```

```

public:
    unsigned short
    month () const;

    void
    month (unsigned short);

    unsigned short
    day () const;

    void
    day (unsigned short);
};

bool
operator== (const gmonth_day&, const gmonth_day&);

bool
operator!= (const gmonth_day&, const gmonth_day&);

```

## 2.5.14 Mapping for gYear

The XML Schema gYear built-in data type is mapped to the `xml_schema::gyear` C++ class which represents a year with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```

class gyear: public simple_type, public time_zone
{
public:
    explicit
    gyear (int year);
    gyear (int year, short zone_hours, short zone_minutes);

public:
    gyear (const gyear&);

    gyear&
    operator= (const gyear&);

    virtual gyear*
    _clone () const;

public:
    int
    year () const;

    void
    year (int);
};

```

```
bool
operator== (const gyear&, const gyear&);
```

```
bool
operator!= (const gyear&, const gyear&);
```

## 2.5.15 Mapping for gYearMonth

The XML Schema gYearMonth built-in data type is mapped to the `xml_schema::gyear_month` C++ class which represents year and month with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```
class gyear_month: public simple_type, public time_zone
{
public:
    gyear_month (int year, unsigned short month);
    gyear_month (int year, unsigned short month,
                 short zone_hours, short zone_minutes);
public:
    gyear_month (const gyear_month&);

    gyear_month&
    operator= (const gyear_month&);

    virtual gyear_month*
    _clone () const;

public:
    int
    year () const;

    void
    year (int);

    unsigned short
    month () const;

    void
    month (unsigned short);
};

bool
operator== (const gyear_month&, const gyear_month&);

bool
operator!= (const gyear_month&, const gyear_month&);
```

## 2.5.16 Mapping for time

The XML Schema time built-in data type is mapped to the `xml_schema::time` C++ class which represents hours, minutes, and seconds with an optional time zone. Its interface is presented below. For more information on the base `xml_schema::time_zone` class refer to Section 2.5.7, "Time Zone Representation".

```
class time: public simple_type, public time_zone
{
public:
    time (unsigned short hours, unsigned short minutes, double seconds);
    time (unsigned short hours, unsigned short minutes, double seconds,
          short zone_hours, short zone_minutes);

public:
    time (const time&);

    time&
    operator= (const time&);

    virtual time*
    _clone () const;

public:
    unsigned short
    hours () const;

    void
    hours (unsigned short);

    unsigned short
    minutes () const;

    void
    minutes (unsigned short);

    double
    seconds () const;

    void
    seconds (double);
};

bool
operator== (const time&, const time&);

bool
operator!= (const time&, const time&);
```

## 2.6 Mapping for Simple Types

An XML Schema simple type is mapped to a C++ class with the same name as the simple type. The class defines a public copy constructor, a public copy assignment operator, and a public virtual `_clone` function. The `_clone` function is declared `const`, does not take any arguments, and returns a pointer to a complete copy of the instance allocated in the free store. The `_clone` function shall be used to make copies when static type and dynamic type of the instance may differ (see Section 2.11, "Mapping for `xsi:type` and Substitution Groups"). For instance:

```
<simpleType name="object">
    ...
</simpleType>
```

is mapped to:

```
class object: ...
{
public:
    object (const object&);

public:
    object&
    operator= (const object&);

public:
    virtual object*
    _clone () const;

    ...
};
```

The base class specification and the rest of the class definition depend on the type of derivation used to define the simple type.

### 2.6.1 Mapping for Derivation by Restriction

XML Schema derivation by restriction is mapped to C++ public inheritance. The base type of the restriction becomes the base type for the resulting C++ class. In addition to the members described in Section 2.6, "Mapping for Simple Types", the resulting C++ class defines a public constructor with the base type as its single argument. For instance:

```
<simpleType name="object">
    <restriction base="base">
        ...
    </restriction>
</simpleType>
```

is mapped to:

```
class object: public base
{
public:
    object (const base&);
    object (const object&);

public:
    object&
    operator= (const object&);

public:
    virtual object*
    _clone () const;
};
```

## 2.6.2 Mapping for Enumerations

XML Schema restriction by enumeration is mapped to a C++ class with semantics similar to C++ enum. Each XML Schema enumeration element is mapped to a C++ enumerator with the name derived from the `value` attribute and defined in the class scope. In addition to the members described in Section 2.6, "Mapping for Simple Types", the resulting C++ class defines a public constructor that can be called with one of the enumerators as its single argument, a public constructor that can be called with enumeration's base value as its single argument, a public assignment operator that can be used to assign the value of one of the enumerators, and a public implicit conversion operator to the underlying C++ enum type.

Furthermore, for string-based enumeration types, the resulting C++ class defines a public constructor with a single argument of type `const C*` and a public constructor with a single argument of type `const std::basic_string<C>&`. For instance:

```
<simpleType name="color">
  <restriction base="string">
    <enumeration value="red"/>
    <enumeration value="green"/>
    <enumeration value="blue"/>
  </restriction>
</simpleType>
```

is mapped to:

```
class color: xml_schema::string
{
public:
    enum value
    {
        red,
```

```

        green,
        blue
    };

public:
    color (value);
    color (const C*);
    color (const std::basic_string<C>&);
    color (const xml_schema::string&);
    color (const color&);

public:
    color&
    operator= (value);

    color&
    operator= (const color&);

public:
    virtual color*
    _clone () const;

public:
    operator value () const;
};

```

## 2.6.3 Mapping for Derivation by List

XML Schema derivation by list is mapped to C++ public inheritance from `xml_schema::simple_type` (Section 2.5.3, "Mapping for anySimpleType") and a suitable sequence type. The list item type becomes the element type of the sequence. In addition to the members described in Section 2.6, "Mapping for Simple Types", the resulting C++ class defines a public default constructor, a public constructor with the first argument of type `size_type` and the second argument of list item type that creates a list object with the specified number of copies of the specified element value, and a public constructor with the two arguments of an input iterator type that creates a list object from an iterator range. For instance:

```

<simpleType name="int_list">
  <list itemType="int"/>
</simpleType>

```

is mapped to:

```

class int_list: public simple_type,
               public sequence<int>
{
public:
    int_list ();
    int_list (size_type n, int x);

```

```

template <typename I>
int_list (const I& begin, const I& end);
int_list (const int_list&);

public:
    int_list&
    operator= (const int_list&);

public:
    virtual int_list*
    _clone () const;
};

```

The sequence class template is defined in an implementation-specific namespace. It conforms to the sequence interface as defined by the ISO/ANSI Standard for C++ (ISO/IEC 14882:1998, Section 23.1.1, "Sequences"). Practically, this means that you can treat such a sequence as if it was `std::vector`. One notable extension to the standard interface that is available only for sequences of non-fundamental C++ types is the addition of the overloaded `push_back` and `insert` member functions which instead of the constant reference to the element type accept automatic pointer to the element type. These functions assume ownership of the pointed to object and resets the passed automatic pointer.

## 2.6.4 Mapping for Derivation by Union

XML Schema derivation by union is mapped to C++ public inheritance from `xml_schema::simple_type` (Section 2.5.3, "Mapping for anySimpleType") and `std::basic_string<C>`. In addition to the members described in Section 2.6, "Mapping for Simple Types", the resulting C++ class defines a public constructor with a single argument of type `const C*` and a public constructor with a single argument of type `const std::basic_string<C>&`. For instance:

```

<simpleType name="int_string_union">
  <xsd:union memberTypes="xsd:int xsd:string"/>
</simpleType>

```

is mapped to:

```

class int_string_union: public simple_type,
                       public std::basic_string<C>
{
public:
    int_string_union (const C*);
    int_string_union (const std::basic_string<C>&);
    int_string_union (const int_string_union&);

public:
    int_string_union&

```

```

operator= (const int_string_union&);

public:
    virtual int_string_union*
    _clone () const;
};

```

## 2.7 Mapping for Complex Types

An XML Schema complex type is mapped to a C++ class with the same name as the complex type. The class defines a public copy constructor, a public copy assignment operator, and a public virtual `_clone` function. The `_clone` function is declared `const`, does not take any arguments, and returns a pointer to a complete copy of the instance allocated in the free store. The `_clone` function shall be used to make copies when static type and dynamic type of the instance may differ (see Section 2.11, "Mapping for `xsi:type` and Substitution Groups").

Additionally, the resulting C++ class defines two public constructors that take an initializer for each member of the complex type and all its base types that belongs to the One cardinality class (see Section 2.8, "Mapping for Local Elements and Attributes"). In the first constructor, the arguments are passed as constant references and the newly created instance is initialized with copies of the passed objects. In the second constructor, arguments that are complex types (that is, they themselves contain elements or attributes) are passed as references to `std::auto_ptr`. In this case the newly created instance is directly initialized with and assumes ownership of the pointed to objects and the `std::auto_ptr` arguments are reset to 0. For instance:

```

<complexType name="complex">
  <sequence>
    <element name="a" type="int"/>
    <element name="b" type="string"/>
  </sequence>
</complexType>

<complexType name="object">
  <sequence>
    <element name="s-one" type="boolean"/>
    <element name="c-one" type="complex"/>
    <element name="optional" type="int" minOccurs="0"/>
    <element name="sequence" type="string" maxOccurs="unbounded"/>
  </sequence>
</complexType>

```

is mapped to:

```

class complex: xml_schema::type
{
public:
    object (const int& a, const xml_schema::string& b);

```

```

    object (const complex&);

public:
    object&
    operator= (const complex&);

public:
    virtual complex*
    _clone () const;

    ...

};

class object: xml_schema::type
{
public:
    object (const bool& s_one, const complex& c_one);
    object (const bool& s_one, std::auto_ptr<complex>& c_one);
    object (const object&);

public:
    object&
    operator= (const object&);

public:
    virtual object*
    _clone () const;

    ...

};

```

Notice that the generated `complex` class does not have the second (`std::auto_ptr`) version of the constructor since all its required members are of simple types.

If an XML Schema complex type has an ultimate base which is an XML Schema simple type then the resulting C++ class also defines a public constructor that takes an initializer for the base type as well as for each member of the complex type and all its base types that belongs to the One cardinality class. For instance:

```

<complexType name="object">
  <simpleContent>
    <extension base="date">
      <attribute name="lang" type="language" use="required"/>
    </extension>
  </simpleContent>
</complexType>

```

is mapped to:

```
class object: xml_schema::string
{
public:
    object (const xml_schema::language& lang);

    object (const xml_schema::date& base,
            const xml_schema::language& lang);

    ...
};
```

Furthermore, for string-based XML Schema complex types, the resulting C++ class also defines two public constructors with the first arguments of type `const C*` and `std::basic_string<C>&`, respectively, followed by arguments for each member of the complex type and all its base types that belongs to the One cardinality class. For enumeration-based complex types the resulting C++ class also defines a public constructor with the first arguments of the underlying enum type followed by arguments for each member of the complex type and all its base types that belongs to the One cardinality class. For instance:

```
<simpleType name="color">
  <restriction base="string">
    <enumeration value="red"/>
    <enumeration value="green"/>
    <enumeration value="blue"/>
  </restriction>
</simpleType>

<complexType name="object">
  <simpleContent>
    <extension base="color">
      <attribute name="lang" type="language" use="required"/>
    </extension>
  </simpleContent>
</complexType>
```

is mapped to:

```
class color: xml_schema::string
{
public:
    enum value
    {
        red,
        green,
        blue
    };
};
```

```

public:
    color (value);
    color (const C*);
    color (const std::basic_string<C>&);

    ...

};

class object: color
{
public:
    object (const color& base,
            const xml_schema::language& lang);

    object (const color::value& base,
            const xml_schema::language& lang);

    object (const C* base,
            const xml_schema::language& lang);

    object (const std::basic_string<C>& base,
            const xml_schema::language& lang);

    ...

};

```

Additional constructors can be requested with the `--generate-default-ctor` and `--generate-from-base-ctor` options. See the XSD Compiler Command Line Manual for details.

If an XML Schema complex type is not explicitly derived from any type, the resulting C++ class is derived from `xml_schema::type`. In cases where an XML Schema complex type is defined using derivation by extension or restriction, the resulting C++ base class specification depends on the type of derivation and is described in the subsequent sections.

The mapping for elements and attributes that are defined in a complex type is described in Section 2.8, "Mapping for Local Elements and Attributes".

## 2.7.1 Mapping for Derivation by Extension

XML Schema derivation by extension is mapped to C++ public inheritance. The base type of the extension becomes the base type for the resulting C++ class.

## 2.7.2 Mapping for Derivation by Restriction

XML Schema derivation by restriction is mapped to C++ public inheritance. The base type of the restriction becomes the base type for the resulting C++ class. XML Schema elements and attributes defined within restriction do not result in any definitions in the resulting C++ class. Instead, corresponding (unrestricted) definitions are inherited from the base class. In the future versions of this mapping, such elements and attributes may result in redefinitions of accessors and modifiers to reflect their restricted semantics.

## 2.8 Mapping for Local Elements and Attributes

XML Schema element and attribute definitions are called local if they appear within a complex type definition, an element group definition, or an attribute group definitions.

Local XML Schema element and attribute definitions have the same C++ mapping. Therefore, in this section, local elements and attributes are collectively called members.

While there are many different member cardinality combinations (determined by the use attribute for attributes and the `minOccurs` and `maxOccurs` attributes for elements), the mapping divides all possible cardinality combinations into three cardinality classes:

*one*

```
attributes: use == "required"
attributes: use == "optional" and has default or fixed value
elements: minOccurs == "1" and maxOccurs == "1"
```

*optional*

```
attributes: use == "optional" and doesn't have default or fixed value
elements: minOccurs == "0" and maxOccurs == "1"
```

*sequence*

```
elements: maxOccurs > "1"
```

An optional attribute with a default or fixed value acquires this value if the attribute hasn't been specified in an instance document (see Appendix A, "Default and Fixed Values"). This mapping places such optional attributes to the One cardinality class.

A member is mapped to a set of public type definitions (`typedefs`) and a set of public accessor and modifier functions. Type definitions have names derived from the member's name. The accessor and modifier functions have the same name as the member. For example:

```
<complexType name="object">
  <sequence>
    <element name="member" type="string"/>
  </sequence>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
    typedef xml_schema::string member_type;

    const member_type&
    member () const;

    ...
};
```

Names and semantics of type definitions for the member as well as signatures of the accessor and modifier functions depend on the member's cardinality class and are described in the following sub-sections.

## 2.8.1 Mapping for Members with the One Cardinality Class

For the One cardinality class, the type definitions consist of an alias for the member's type with the name created by appending the `_type` suffix to the member's name.

The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to the member and can be used for read-only access. The non-constant version returns an unrestricted reference to the member and can be used for read-write access.

The first modifier function expects an argument of type reference to constant of the member's type. It makes a deep copy of its argument. Except for member's types that are mapped to fundamental C++ types, the second modifier function is provided that expects an argument of type automatic pointer to the member's type. It assumes ownership of the pointed to object and resets the passed automatic pointer. For instance:

```
<complexType name="object">
  <sequence>
    <element name="member" type="string"/>
  </sequence>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
    // Type definitions.
    //
    typedef xml_schema::string member_type;
```

```

// Accessors.
//
const member_type&
member () const;

member_type&
member ();

// Modifiers.
//
void
member (const member_type&);

void
member (std::auto_ptr<member_type>);
...
};

```

The following code shows how one could use this mapping:

```

void
f (object& o)
{
    using xml_schema::string;

    string s (o.member ()); // get
    object::member_type& sr (o.member ()); // get

    o.member ("hello"); // set, deep copy
    o.member () = "hello"; // set, deep copy

    std::auto_ptr<string> p (new string ("hello"));
    o.member (p); // set, assumes ownership
}

```

## 2.8.2 Mapping for Members with the Optional Cardinality Class

For the Optional cardinality class, the type definitions consist of an alias for the member's type with the name created by appending the `_type` suffix to the member's name and an alias for the container type with the name created by appending the `_optional` suffix to the member's name.

Unlike accessor functions for the One cardinality class, accessor functions for the Optional cardinality class return references to corresponding containers rather than directly to members. The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to the container and can be used for read-only access. The non-constant version returns an unrestricted reference to the container and can be used for

read-write access.

The modifier functions are overloaded for the member's type and the container type. The first modifier function expects an argument of type reference to constant of the member's type. It makes a deep copy of its argument. Except for member's types that are mapped to fundamental C++ types, the second modifier function is provided that expects an argument of type automatic pointer to the member's type. It assumes ownership of the pointed to object and resets the passed automatic pointer. The last modifier function expects an argument of type reference to constant of the container type. It makes a deep copy of its argument. For instance:

```
<complexType name="object">
  <sequence>
    <element name="member" type="string" minOccurs="0"/>
  </sequence>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
    // Type definitions.
    //
    typedef xml_schema::string member_type;
    typedef optional<member_type> member_optional;

    // Accessors.
    //
    const member_optional&
    member () const;

    member_optional&
    member ();

    // Modifiers.
    //
    void
    member (const member_type&);

    void
    member (std::auto_ptr<member_type>);

    void
    member (const member_optional&);

    ...
};
```

The optional class template is defined in an implementation-specific namespace and has the following interface. The `auto_ptr`-based constructor and modifier function are only available if the template argument is not a fundamental C++ type.

```
template <typename X>
class optional
{
public:
    optional ();

    // Makes a deep copy.
    //
    explicit
    optional (const X&);

    // Assumes ownership.
    //
    explicit
    optional (std::auto_ptr<X>);

    optional (const optional&);

public:
    optional&
    operator= (const X&);

    optional&
    operator= (const optional&);

    // Pointer-like interface.
    //
public:
    const X*
    operator-> () const;

    X*
    operator-> ();

    const X&
    operator* () const;

    X&
    operator* ();

    typedef void (optional::*bool_convertible) ();
    operator bool_convertible () const;

    // Get/set interface.
    //
public:
    bool
```

```

    present () const;

    const X&
    get () const;

    X&
    get ();

    // Makes a deep copy.
    //
    void
    set (const X&);

    // Assumes ownership.
    //
    void
    set (std::auto_ptr<X>);

    void
    reset ();
};

template <typename X>
bool
operator== (const optional<X>&, const optional<X>&);

template <typename X>
bool
operator!= (const optional<X>&, const optional<X>&);

template <typename X>
bool
operator< (const optional<X>&, const optional<X>&);

template <typename X>
bool
operator> (const optional<X>&, const optional<X>&);

template <typename X>
bool
operator<= (const optional<X>&, const optional<X>&);

template <typename X>
bool
operator>= (const optional<X>&, const optional<X>&);

```

The following code shows how one could use this mapping:

```

void
f (object& o)
{
    using xml_schema::string;

    if (o.member ().present ())          // test
    {
        string& s (o.member ().get ()); // get
        o.member ("hello");             // set, deep copy
        o.member ().set ("hello");      // set, deep copy
        o.member ().reset ();           // reset
    }

    // Same as above but using pointer notation:
    //
    if (o.member ())                    // test
    {
        string& s (*o.member ());      // get
        o.member ("hello");             // set, deep copy
        *o.member () = "hello";        // set, deep copy
        o.member ().reset ();           // reset
    }

    std::auto_ptr<string> p (new string ("hello"));
    o.member (p);                       // set, assumes ownership

    p = new string ("hello");
    o.member ().set (p);                 // set, assumes ownership
}

```

## 2.8.3 Mapping for Members with the Sequence Cardinality Class

For the Sequence cardinality class, the type definitions consist of an alias for the member's type with the name created by appending the `_type` suffix to the member's name, an alias of the container type with the name created by appending the `_sequence` suffix to the member's name, an alias of the iterator type with the name created by appending the `_iterator` suffix to the member's name, and an alias of the constant iterator type with the name created by appending the `_const_iterator` suffix to the member's name.

The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to the container and can be used for read-only access. The non-constant version returns an unrestricted reference to the container and can be used for read-write access.

The modifier function expects an argument of type reference to constant of the container type. The modifier function makes a deep copy of its argument. For instance:

```
<complexType name="object">
  <sequence>
    <element name="member" type="string" minOccurs="unbounded"/>
  </sequence>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
  // Type definitions.
  //
  typedef xml_schema::string member_type;
  typedef sequence<member_type> member_sequence;
  typedef member_sequence::iterator member_iterator;
  typedef member_sequence::const_iterator member_const_iterator;

  // Accessors.
  //
  const member_sequence&
  member () const;

  member_sequence&
  member ();

  // Modifier.
  //
  void
  member (const member_sequence&);

  ...
};
```

The sequence class template is defined in an implementation-specific namespace. It conforms to the sequence interface as defined by the ISO/ANSI Standard for C++ (ISO/IEC 14882:1998, Section 23.1.1, "Sequences"). Practically, this means that you can treat such a sequence as if it was `std::vector`. One notable extension to the standard interface that is available only for sequences of non-fundamental C++ types is the addition of the overloaded `push_back` and `insert` member functions which instead of the constant reference to the element type accept automatic pointer to the element type. These functions assume ownership of the pointed to object and resets the passed automatic pointer.

The following code shows how one could use this mapping:

```

void
f (object& o)
{
    using xml_schema::string;

    object::member_sequence& s (o.member ());

    // Iteration.
    //
    for (object::member_iterator i (s.begin ()); i != s.end (); ++i)
    {
        string& value (*i);
    }

    // Modification.
    //
    s.push_back ("hello"); // deep copy

    std::auto_ptr<string> p (new string ("hello"));
    s.push_back (o); // assumes ownership

    // Setting a new container.
    //
    object::member_sequence n;
    n.push_back ("one");
    n.push_back ("two");
    o.member (n); // deep copy
}

```

## 2.9 Mapping for Global Elements

An XML Schema element definition is called global if it appears directly under the schema element. A global element is a valid root of an instance document. As such, it is mapped to a set of overloaded parsing and, optionally, serialization functions with the same name as the element.

The parsing functions read XML instance documents and return corresponding object models. Their signatures have the following pattern (type denotes element's type and name denotes element's name):

```

std::auto_ptr<type>
name (...);

```

The process of parsing, including the exact signatures of the parsing functions, is the subject of Chapter 3, "Parsing".

The serialization functions write object models back to XML instance documents. Their signatures have the following pattern:

```
void
name (<stream type>&, const type&, ....);
```

The process of serialization, including the exact signatures of the serialization functions, is the subject of Chapter 4, "Serialization".

## 2.10 Mapping for Global Attributes

An XML Schema attribute definition is called global if it appears directly under the schema element. A global attribute does not have any mapping.

## 2.11 Mapping for `xsi:type` and Substitution Groups

The mapping provides optional support for the XML Schema polymorphism features (`xsi:type` and substitution groups) which can be requested with the `--generate-polymorphic` option. When used, the dynamic type of a member may be different from its static type. Consider the following schema definition and instance document:

```
<!-- test.xsd -->
<schema>
  <complexType name="base">
    <attribute name="text" type="string"/>
  </complexType>

  <complexType name="derived">
    <complexContent>
      <extension base="base">
        <attribute name="extra-text" type="string"/>
      </extension>
    </complexContent>
  </complexType>

  <complexType name="root_type">
    <sequence>
      <element name="item" type="base" maxOccurs="unbounded"/>
    </sequence>
  </complexType>

  <element name="root" type="root_type"/>
</schema>

<!-- test.xml -->
<root xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
  <item text="hello"/>
  <item text="hello" extra-text="world" xsi:type="derived"/>
</root>
```

In the resulting object model, the container for the `root::item` member will have two elements: the first element's type will be `base` while the second element's (dynamic) type will be derived. This can be discovered using the `dynamic_cast` operator as shown in the following example:

```
void
f (root& r)
{
    for (root::item_const_iterator i (r.item ().begin ());
        i != r.item ().end ()
        ++i)
    {
        if (derived* d = dynamic_cast<derived*> (&(*i)))
        {
            // derived
        }
        else
        {
            // base
        }
    }
}
```

The `_clone` virtual function should be used instead of copy constructors to make copies of members that might use polymorphism:

```
void
f (root& r)
{
    for (root::item_const_iterator i (r.item ().begin ());
        i != r.item ().end ()
        ++i)
    {
        std::auto_ptr<base> c (i->_clone ());
    }
}
```

## 2.12 Mapping for any and anyAttribute

For the XML Schema `any` and `anyAttribute` wildcards an optional mapping can be requested with the `--generate-wildcard` option. The mapping represents the content matched by wildcards as DOM fragments. Because the DOM API is used to access such content, the Xerces-C++ runtime should be initialized by the application prior to parsing and should remain initialized for the lifetime of objects with the wildcard content. For more information on the Xerces-C++ runtime initialization see Section 3.1, "Initializing the Xerces-C++ Runtime".

The mapping for `any` is similar to the mapping for local elements (see Section 2.8, "Mapping for Local Elements and Attributes") except that the type used in the wildcard mapping is `xercesc::DOMElement`. As with local elements, the mapping divides all possible cardinality combinations into three cardinality classes: *one*, *optional*, and *sequence*.

The mapping for `anyAttribute` represents the attributes matched by this wildcard as a set of `xercesc::DOMAttr` objects with a key being the attribute's name and namespace.

Similar to local elements and attributes, the `any` and `anyAttribute` wildcards are mapped to a set of public type definitions (typedefs) and a set of public accessor and modifier functions. Type definitions have names derived from "any" for the `any` wildcard and "any\_attribute" for the `anyAttribute` wildcard. The accessor and modifier functions are named "any" for the `any` wildcard and "any\_attribute" for the `anyAttribute` wildcard. Subsequent wildcards in the same type have escaped names such as "any1" or "any\_attribute1".

Because Xerces-C++ DOM nodes always belong to a `DOMDocument`, each type with a wildcard has an associated `DOMDocument` object. The reference to this object can be obtained using the accessor function called `dom_document`. The access to the document object from the application code may be necessary to create or modify the wildcard content. For example:

```
<complexType name="object">
  <sequence>
    <any namespace="##other"/>
  </sequence>
  <anyAttribute namespace="##other"/>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
    // any
    //
    const xercesc::DOMElement&
    any () const;

    void
    any (const xercesc::DOMElement&);

    ...

    // any_attribute
    //
    typedef attribute_set any_attribute_set;
    typedef any_attribute_set::iterator any_attribute_iterator;
    typedef any_attribute_set::const_iterator any_attribute_const_iterator;
```

```

const any_attribute_set&
any_attribute () const;

any_attribute_set&
any_attribute ();

...

// DOMDocument object for wildcard content.
//
const xercesc::DOMDocument&
dom_document () const;

xercesc::DOMDocument&
dom_document ();

...
};

```

Names and semantics of type definitions for the wildcards as well as signatures of the accessor and modifier functions depend on the wildcard type as well as the cardinality class for the any wildcard. They are described in the following sub-sections.

### 2.12.1 Mapping for any with the One Cardinality Class

For any with the One cardinality class, there are no type definitions. The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to `xercesc::DOMElement` and can be used for read-only access. The non-constant version returns an unrestricted reference to `xercesc::DOMElement` and can be used for read-write access.

The first modifier function expects an argument of type reference to constant `xercesc::DOMElement` and makes a deep copy of its argument. The second modifier function expects an argument of type pointer to `xercesc::DOMElement`. This modifier function assumes ownership of its argument and expects the element object to be created using the DOM document associated with this instance. For example:

```

<complexType name="object">
  <sequence>
    <any namespace="##other"/>
  </sequence>
</complexType>

```

is mapped to:

```

class object: xml_schema::type
{
public:
    // Accessors.
    //
    const xercesc::DOMElement&
    any () const;

    xercesc::DOMElement&
    any ();

    // Modifiers.
    //
    void
    any (const xercesc::DOMElement&);

    void
    any (xercesc::DOMElement*);

    ...
};

```

The following code shows how one could use this mapping:

```

void
f (object& o, const xercesc::DOMElement& e)
{
    using namespace xercesc;

    DOMElement& el (o.any ());           // get
    o.any (e)                               // set, deep copy
    DOMDocument& doc (o.dom_document ());
    o.any (doc.createElement (...));      // set, assumes ownership
}

```

## 2.12.2 Mapping for any with the Optional Cardinality Class

For any with the Optional cardinality class, the type definitions consist of an alias for the container type with name `any_optional` (or `any1_optional`, etc., for subsequent wild-cards in the type definition).

Unlike accessor functions for the One cardinality class, accessor functions for the Optional cardinality class return references to corresponding containers rather than directly to `DOMElement`. The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to the container and can be used for read-only access. The non-constant version returns an unrestricted reference to the container and can be used for read-write access.

The modifier functions are overloaded for `xercesc::DOMElement` and the container type. The first modifier function expects an argument of type reference to constant `xercesc::DOMElement` and makes a deep copy of its argument. The second modifier function expects an argument of type pointer to `xercesc::DOMElement`. This modifier function assumes ownership of its argument and expects the element object to be created using the DOM document associated with this instance. The third modifier function expects an argument of type reference to constant of the container type and makes a deep copy of its argument. For instance:

```
<complexType name="object">
  <sequence>
    <any namespace="##other" minOccurs="0"/>
  </sequence>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
  // Type definitions.
  //
  typedef element_optional any_optional;

  // Accessors.
  //
  const any_optional&
  any () const;

  any_optional&
  any ();

  // Modifiers.
  //
  void
  any (const xercesc::DOMElement&);

  void
  any (xercesc::DOMElement*);

  void
  any (const any_optional&);

  ...
};
```

The `element_optional` container is a specialization of the `optional` class template described in Section 2.8.2, "Mapping for Members with the Optional Cardinality Class". Its interface is presented below:

```

class element_optional
{
public:
    explicit
    element_optional (xercesc::DOMDocument&);

    // Makes a deep copy.
    //
    element_optional (const xercesc::DOMElement&, xercesc::DOMDocument&);

    // Assumes ownership.
    //
    element_optional (xercesc::DOMElement*, xercesc::DOMDocument&);

    element_optional (const element_optional&, xercesc::DOMDocument&);

public:
    element_optional&
    operator= (const xercesc::DOMElement&);

    element_optional&
    operator= (const element_optional&);

    // Pointer-like interface.
    //
public:
    const xercesc::DOMElement*
    operator-> () const;

    xercesc::DOMElement*
    operator-> ();

    const xercesc::DOMElement&
    operator* () const;

    xercesc::DOMElement&
    operator* ();

    typedef void (element_optional::*bool_convertible) ();
    operator bool_convertible () const;

    // Get/set interface.
    //
public:
    bool
    present () const;

    const xercesc::DOMElement&
    get () const;

    xercesc::DOMElement&

```

```

get ();

// Makes a deep copy.
//
void
set (const xercesc::DOMElement&);

// Assumes ownership.
//
void
set (xercesc::DOMElement*);

void
reset ();
};

bool
operator== (const element_optional&, const element_optional&);

bool
operator!= (const element_optional&, const element_optional&);

```

The following code shows how one could use this mapping:

```

void
f (object& o, const xercesc::DOMElement& e)
{
    using namespace xercesc;

    DOMDocument& doc (o.dom_document ());

    if (o.any ().present ())                // test
    {
        DOMElement& el (o.any ().get ());    // get
        o.any ().set (e);                    // set, deep copy
        o.any ().set (doc.createElement (...)); // set, assumes ownership
        o.any ().reset ();                  // reset
    }

    // Same as above but using pointer notation:
    //
    if (o.member ())                        // test
    {
        DOMElement& el (*o.any ());          // get
        o.any (e);                          // set, deep copy
        o.any (doc.createElement (...));    // set, assumes ownership
        o.any ().reset ();                  // reset
    }
}

```

## 2.12.3 Mapping for any with the Sequence Cardinality Class

For any with the Sequence cardinality class, the type definitions consist of an alias of the container type with name `any_sequence` (or `any1_sequence`, etc., for subsequent wildcards in the type definition), an alias of the iterator type with name `any_iterator` (or `any1_iterator`, etc., for subsequent wildcards in the type definition), and an alias of the constant iterator type with name `any_const_iterator` (or `any1_const_iterator`, etc., for subsequent wildcards in the type definition).

The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to the container and can be used for read-only access. The non-constant version returns an unrestricted reference to the container and can be used for read-write access.

The modifier function expects an argument of type reference to constant of the container type. The modifier function makes a deep copy of its argument. For instance:

```
<complexType name="object">
  <sequence>
    <any namespace="##other" minOccurs="unbounded"/>
  </sequence>
</complexType>
```

is mapped to:

```
class object: xml_schema::type
{
public:
    // Type definitions.
    //
    typedef element_sequence any_sequence;
    typedef any_sequence::iterator any_iterator;
    typedef any_sequence::const_iterator any_const_iterator;

    // Accessors.
    //
    const any_sequence&
    any () const;

    any_sequence&
    any ();

    // Modifier.
    //
    void
    any (const any_sequence&);
```

```
...
};
```

The `element_sequence` container is a specialization of the `sequence` class template described in Section 2.8.3, "Mapping for Members with the Sequence Cardinality Class". Its interface is similar to the `sequence` interface as defined by the ISO/ANSI Standard for C++ (ISO/IEC 14882:1998, Section 23.1.1, "Sequences") and is presented below:

```
class element_sequence
{
public:
    typedef xercesc::DOMElement      value_type;
    typedef xercesc::DOMElement*     pointer;
    typedef const xercesc::DOMElement* const_pointer;
    typedef xercesc::DOMElement&     reference;
    typedef const xercesc::DOMElement& const_reference;

    typedef <implementation-defined> iterator;
    typedef <implementation-defined> const_iterator;
    typedef <implementation-defined> reverse_iterator;
    typedef <implementation-defined> const_reverse_iterator;

    typedef <implementation-defined> size_type;
    typedef <implementation-defined> difference_type;
    typedef <implementation-defined> allocator_type;

public:
    explicit
    element_sequence (xercesc::DOMDocument&);

    // DOMElement cannot be default-constructed.
    //
    // explicit
    // element_sequence (size_type n);

    element_sequence (size_type n,
                     const xercesc::DOMElement&,
                     xercesc::DOMDocument&);

    template <typename I>
    element_sequence (const I& begin,
                     const I& end,
                     xercesc::DOMDocument&);

    element_sequence (const element_sequence&, xercesc::DOMDocument&);

    element_sequence&
    operator= (const element_sequence&);
```

```

public:
    void
    assign (size_type n, const xercesc::DOMElement&);

    template <typename I>
    void
    assign (const I& begin, const I& end);

public:
    // This version of resize can only be used to shrink the
    // sequence because DOMElement cannot be default-constructed.
    //
    void
    resize (size_type);

    void
    resize (size_type, const xercesc::DOMElement&);

public:
    size_type
    size () const;

    size_type
    max_size () const;

    size_type
    capacity () const;

    bool
    empty () const;

    void
    reserve (size_type);

    void
    clear ();

public:
    const_iterator
    begin () const;

    const_iterator
    end () const;

    iterator
    begin ();

    iterator
    end ();

```

```

const_reverse_iterator
rbegin () const;

const_reverse_iterator
rend () const

    reverse_iterator
rbegin ();

reverse_iterator
rend ();

public:
    xercesc::DOMElement&
operator[] (size_type);

    const xercesc::DOMElement&
operator[] (size_type) const;

    xercesc::DOMElement&
at (size_type);

    const xercesc::DOMElement&
at (size_type) const;

    xercesc::DOMElement&
front ();

    const xercesc::DOMElement&
front () const;

    xercesc::DOMElement&
back ();

    const xercesc::DOMElement&
back () const;

public:
    // Makes a deep copy.
    //
    void
push_back (const xercesc::DOMElement&);

    // Assumes ownership.
    //
    void
push_back (xercesc::DOMElement*);

    void
pop_back ();

```

```

// Makes a deep copy.
//
iterator
insert (iterator position, const xercesc::DOMElement&);

// Assumes ownership.
//
iterator
insert (iterator position, xercesc::DOMElement*);

void
insert (iterator position, size_type n, const xercesc::DOMElement&);

template <typename I>
void
insert (iterator position, const I& begin, const I& end);

iterator
erase (iterator position);

iterator
erase (iterator begin, iterator end);

public:
// Note that the DOMDocument object of the two sequences being
// swapped should be the same.
//
void
swap (sequence& x);
};

inline bool
operator== (const element_sequence&, const element_sequence&);

inline bool
operator!= (const element_sequence&, const element_sequence&);

```

The following code shows how one could use this mapping:

```

void
f (object& o, const xercesc::DOMElement& e)
{
    using namespace xercesc;

    object::any_sequence& s (o.any ());

    // Iteration.
    //
    for (object::any_iterator i (s.begin ()); i != s.end (); ++i)
    {
        DOMElement& e (*i);
    }
}

```

```

}

// Modification.
//
s.push_back (e); // deep copy
DOMDocument& doc (o.dom_document ());
s.push_back (doc.createElement (...)); // assumes ownership
}

```

## 2.12.4 Mapping for anyAttribute

For anyAttribute the type definitions consist of an alias of the container type with name any\_attribute\_set (or any1\_attribute\_set, etc., for subsequent wildcards in the type definition), an alias of the iterator type with name any\_attribute\_iterator (or any1\_attribute\_iterator, etc., for subsequent wildcards in the type definition), and an alias of the constant iterator type with name any\_attribute\_const\_iterator (or any1\_attribute\_const\_iterator, etc., for subsequent wildcards in the type definition).

The accessor functions come in constant and non-constant versions. The constant accessor function returns a constant reference to the container and can be used for read-only access. The non-constant version returns an unrestricted reference to the container and can be used for read-write access.

The modifier function expects an argument of type reference to constant of the container type. The modifier function makes a deep copy of its argument. For instance:

```

<complexType name="object">
  <sequence>
    ...
  </sequence>
  <anyAttribute namespace="##other"/>
</complexType>

```

is mapped to:

```

class object: xml_schema::type
{
public:
  // Type definitions.
  //
  typedef attribute_set any_attribute_set;
  typedef any_attribute_set::iterator any_attribute_iterator;
  typedef any_attribute_set::const_iterator any_attribute_const_iterator;

  // Accessors.
  //
  const any_attribute_set&
  any_attribute () const;

```

```

any_attribute_set&
any_attribute ();

// Modifier.
//
void
any_attribute (const any_attribute_set&);

...

};

```

The `attribute_set` class is an associative container similar to the `std::set` class template as defined by the ISO/ANSI Standard for C++ (ISO/IEC 14882:1998, Section 23.3.3, "Class template set") with the key being the attribute's name and namespace. Unlike `std::set`, `attribute_set` allows searching using names and namespaces instead of `xercesc::DOMAttr` objects. It is defined in an implementation-specific namespace and its interface is presented below:

```

class attribute_set
{
public:
    typedef xercesc::DOMAttr      key_type;
    typedef xercesc::DOMAttr      value_type;
    typedef xercesc::DOMAttr*     pointer;
    typedef const xercesc::DOMAttr* const_pointer;
    typedef xercesc::DOMAttr&     reference;
    typedef const xercesc::DOMAttr& const_reference;

    typedef <implementation-defined> iterator;
    typedef <implementation-defined> const_iterator;
    typedef <implementation-defined> reverse_iterator;
    typedef <implementation-defined> const_reverse_iterator;

    typedef <implementation-defined> size_type;
    typedef <implementation-defined> difference_type;
    typedef <implementation-defined> allocator_type;

public:
    attribute_set (xercesc::DOMDocument&);

    template <typename I>
    attribute_set (const I& begin, const I& end, xercesc::DOMDocument&);

    attribute_set (const attribute_set&, xercesc::DOMDocument&);

    attribute_set&
    operator= (const attribute_set&);

```

```

public:
    const_iterator
    begin () const;

    const_iterator
    end () const;

    iterator
    begin ();

    iterator
    end ();

    const_reverse_iterator
    rbegin () const;

    const_reverse_iterator
    rend () const;

    reverse_iterator
    rbegin ();

    reverse_iterator
    rend ();

public:
    size_type
    size () const;

    size_type
    max_size () const;

    bool
    empty () const;

    void
    clear ();

public:
    // Makes a deep copy.
    //
    std::pair<iterator, bool>
    insert (const xercesc::DOMAttr&);

    // Assumes ownership.
    //
    std::pair<iterator, bool>
    insert (xercesc::DOMAttr*);

    // Makes a deep copy.
    //

```

```

    iterator
    insert (iterator position, const xercesc::DOMAttr&);

    // Assumes ownership.
    //
    iterator
    insert (iterator position, xercesc::DOMAttr*);

    template <typename I>
    void
    insert (const I& begin, const I& end);

public:
    void
    erase (iterator position);

    size_type
    erase (const std::basic_string<C>& name);

    size_type
    erase (const std::basic_string<C>& namespace_,
           const std::basic_string<C>& name);

    size_type
    erase (const XMLCh* name);

    size_type
    erase (const XMLCh* namespace_, const XMLCh* name);

    void
    erase (iterator begin, iterator end);

public:
    size_type
    count (const std::basic_string<C>& name) const;

    size_type
    count (const std::basic_string<C>& namespace_,
           const std::basic_string<C>& name) const;

    size_type
    count (const XMLCh* name) const;

    size_type
    count (const XMLCh* namespace_, const XMLCh* name) const;

    iterator
    find (const std::basic_string<C>& name);

    iterator
    find (const std::basic_string<C>& namespace_,

```

```

        const std::basic_string<C>& name);

iterator
find (const XMLCh* name);

iterator
find (const XMLCh* namespace_, const XMLCh* name);

const_iterator
find (const std::basic_string<C>& name) const;

const_iterator
find (const std::basic_string<C>& namespace_,
      const std::basic_string<C>& name) const;

const_iterator
find (const XMLCh* name) const;

const_iterator
find (const XMLCh* namespace_, const XMLCh* name) const;

public:
    // Note that the DOMDocument object of the two sets being
    // swapped should be the same.
    //
    void
    swap (attribute_set&);
};

bool
operator== (const attribute_set&, const attribute_set&);

bool
operator!= (const attribute_set&, const attribute_set&);

```

The following code shows how one could use this mapping:

```

void
f (object& o, const xercesc::DOMAttr& a)
{
    using namespace xercesc;

    object::any_attribute_set& s (o.any_attribute ());

    // Iteration.
    //
    for (object::any_attribute_iterator i (s.begin ()); i != s.end (); ++i)
    {
        DOMAttr& a (*i);
    }
}

```

```

// Modification.
//
s.insert (a); // deep copy
DOMDocument& doc (o.dom_document ());
s.insert (doc.createAttribute (...)); // assumes ownership

// Searching.
//
object::any_attribute_iterator i (s.find ("name"));
i = s.find ("http://www.w3.org/XML/1998/namespace", "lang");
}

```

## 2.13 Mapping for Mixed Content Models

XML Schema mixed content models do not have a direct C++ mapping. Instead, information in XML instance documents, corresponding to a mixed content model, can be accessed using generic DOM nodes that can optionally be associated with object model nodes. See Section 5.1, "DOM Association" for more information about keeping association with DOM nodes.

## 3 Parsing

This chapter covers various aspects of parsing XML instance documents in order to obtain corresponding tree-like object model.

Each global XML Schema element in the form:

```
<element name="name" type="type"/>
```

is mapped to 14 overloaded C++ functions in the form:

```

// Read from a URI or a local file.
//

std::auto_ptr<type>
name (const std::basic_string<C>& uri,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (const std::basic_string<C>& uri,
      xml_schema::error_handler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (const std::basic_string<C>& uri,
      xercesc::DOMErrorHandler&,
      xml_schema::flags = 0,

```

```

        const xml_schema::properties& = xml_schema::properties ();

// Read from std::istream.
//

std::auto_ptr<type>
name (std::istream&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (std::istream&,
      xml_schema::error_handler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (std::istream&,
      xercesc::DOMErrorHandler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (std::istream&,
      const std::basic_string<C>& id,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (std::istream&,
      const std::basic_string<C>& id,
      xml_schema::error_handler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (std::istream&,
      const std::basic_string<C>& id,
      xercesc::DOMErrorHandler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

// Read from InputSource.
//

std::auto_ptr<type>
name (xercesc::InputSource&,
      xml_schema::flags = 0,

```

```

        const xml_schema::properties& = xml_schema::properties ();

std::auto_ptr<type>
name (xercesc::InputSource&,
      xml_schema::error_handler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (xercesc::InputSource&,
      xercesc::DOMErrorHandler&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

// Read from DOM.
//

std::auto_ptr<type>
name (const xercesc::DOMDocument&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

std::auto_ptr<type>
name (xml_schema::dom::auto_ptr<xercesc::DOMDocument>&,
      xml_schema::flags = 0,
      const xml_schema::properties& = xml_schema::properties ());

```

You can choose between reading an XML instance from a local file, URI, `std::istream`, `xercesc::InputSource`, or a pre-parsed DOM instance in the form of `xercesc::DOMDocument`. Each of these parsing functions is discussed in more detail in the following sections.

## 3.1 Initializing the Xerces-C++ Runtime

Some parsing functions expect you to initialize the Xerces-C++ runtime while others initialize and terminate it as part of their work. The general rule is as follows: if a function has any arguments or return a value that is an instance of a Xerces-C++ type, then this function expects you to initialize the Xerces-C++ runtime. Otherwise, the function initializes and terminates the runtime for you. Note that it is legal to have nested calls to the Xerces-C++ initialize and terminate functions as long as the calls are balanced.

You can instruct parsing functions that initialize and terminate the runtime not to do so by passing the `xml_schema::flags::dont_initialize` flag (see Section 3.2, "Flags and Properties").

## 3.2 Flags and Properties

Parsing flags and properties are the last two arguments of every parsing function. They allow you to fine-tune the process of instance validation and parsing. Both arguments are optional.

The following flags are recognized by the parsing functions:

`xml_schema::flags::keep_dom`

Keep association between DOM nodes and the resulting object model nodes. For more information about DOM association refer to Section 5.1, "DOM Association".

`xml_schema::flags::own_dom`

Assume ownership of the DOM document passed. This flag only makes sense together with the `keep_dom` flag in the call to the parsing function with the `xml_schema::dom::auto_ptr<DOMDocument>` argument.

`xml_schema::flags::dont_validate`

Do not validate instance documents against schemas.

`xml_schema::flags::dont_initialize`

Do not initialize the Xerces-C++ runtime.

You can pass several flags by combining them using the bit-wise OR operator. For example:

```
using xml_schema::flags;

std::auto_ptr<type> r (
    name ("test.xml", flags::keep_dom | flags::dont_validate));
```

By default, validation of instance documents is turned on even though parsers generated by XSD do not assume instance documents are valid. They include a number of checks that prevent construction of inconsistent object models. This, however, does not mean that an instance document that was successfully parsed by the XSD-generated parsers is valid per the corresponding schema. If an instance document is not "valid enough" for the generated parsers to construct consistent object model, one of the exceptions defined in `xml_schema` namespace is thrown (see Section 3.3, "Error Handling").

For more information on the Xerces-C++ runtime initialization refer to Section 3.1, "Initializing the Xerces-C++ Runtime".

The `xml_schema::properties` class allows you to programmatically specify schema locations to be used instead of those specified with the `xsi::schemaLocation` and `xsi::noNamespaceSchemaLocation` attributes in instance documents. The interface of the `properties` class is presented below:

```

class properties
{
public:
    void
        schema_location (const std::basic_string<C>& namespace_,
                        const std::basic_string<C>& location);

    void
        no_namespace_schema_location (const std::basic_string<C>& location);
};

```

Note that all locations are relative to an instance document unless they are URIs. For example, if you want to use a local file as your schema, then you will need to pass `file:///absolute/path/to/your/schema` as the location argument.

### 3.3 Error Handling

As discussed in Section 2.2, "Error Handling", the mapping uses the C++ exception handling mechanism as its primary way of reporting error conditions. However, to handle recoverable parsing and validation errors and warnings, a callback interface maybe preferred by the application.

To better understand error handling and reporting strategies employed by the parsing functions, it is useful to know that the transformation of an XML instance document to a statically-typed tree happens in two stages. The first stage, performed by Xerces-C++, consists of parsing an XML document into a DOM instance. For short, we will call this stage the XML-DOM stage. Validation, if not disabled, happens during this stage. The second stage, performed by the generated parsers, consist of parsing the DOM instance into the statically-typed tree. We will call this stage the DOM-Tree stage. Additional checks are performed during this stage in order to prevent construction of inconsistent tree which could otherwise happen when validation is disabled, for example.

All parsing functions except the one that operates on a DOM instance come in overloaded triples. The first function in such a triple reports error conditions exclusively by throwing exceptions. It accumulates all the parsing and validation errors of the XML-DOM stage and throws them in a single instance of the `xml_schema::parsing` exception (described below). The second and the third functions in the triple use callback interfaces to report parsing and validation errors and warnings. The two callback interfaces are `xml_schema::error_handler` and `xercesc::DOMErrorHandler`. For more information on the `xercesc::DOMErrorHandler` interface refer to the Xerces-C++ documentation. The `xml_schema::error_handler` interface is presented below:

```

class error_handler
{
public:
    struct severity

```

```

{
    enum value
    {
        warning,
        error,
        fatal
    };
};

virtual bool
handle (const std::basic_string<C>& id,
        unsigned long line,
        unsigned long column,
        severity,
        const std::basic_string<C>& message) = 0;

virtual
~error_handler ();
};

```

The `id` argument of the `error_handler::handle` function identifies the resource being parsed (e.g., a file name or URI).

By returning `true` from the `handle` function you instruct the parser to recover and continue parsing. Returning `false` results in termination of the parsing process. An error with the `fatal` severity level results in termination of the parsing process no matter what is returned from the `handle` function. It is safe to throw an exception from the `handle` function.

The DOM-Tree stage reports error conditions exclusively by throwing exceptions. Individual exceptions thrown by the parsing functions are described in the following sub-sections.

### 3.3.1 xml\_schema::parsing

```

struct severity
{
    enum value
    {
        warning,
        error
    };

    severity (value);
    operator value () const;
};

struct error
{
    error (severity,
          const std::basic_string<C>& id,

```

```

        unsigned long line,
        unsigned long column,
        const std::basic_string<C>& message);

    severity
    severity () const;

    const std::basic_string<C>&
    id () const;

    unsigned long
    line () const;

    unsigned long
    column () const;

    const std::basic_string<C>&
    message () const;
};

std::basic_ostream<C>&
operator<< (std::basic_ostream<C>&, const error&);

struct diagnostics: std::vector<error>
{
};

std::basic_ostream<C>&
operator<< (std::basic_ostream<C>&, const diagnostics&);

struct parsing: virtual exception
{
    parsing ();
    parsing (const diagnostics&);

    const diagnostics&
    diagnostics () const;

    virtual const char*
    what () const throw ();
};

```

The `xml_schema::parsing` exception is thrown if there were parsing or validation errors reported during the XML-DOM stage. If no callback interface was provided to the parsing function, the exception contains a list of errors and warnings accessible using the `diagnostics` function. The usual conditions when this exception is thrown include malformed XML instances and, if validation is turned on, invalid instance documents.

### 3.3.2 xml\_schema::expected\_element

```
struct expected_element: virtual exception
{
    expected_element (const std::basic_string<C>& name,
                     const std::basic_string<C>& namespace_);

    const std::basic_string<C>&
    name () const;

    const std::basic_string<C>&
    namespace_ () const;

    virtual const char*
    what () const throw ();
};
```

The `xml_schema::expected_element` exception is thrown when an expected element is not encountered by the DOM-Tree stage. The name and namespace of the expected element can be obtained using the `name` and `namespace_` functions respectively.

### 3.3.3 xml\_schema::unexpected\_element

```
struct unexpected_element: virtual exception
{
    unexpected_element (const std::basic_string<C>& encountered_name,
                       const std::basic_string<C>& encountered_namespace,
                       const std::basic_string<C>& expected_name,
                       const std::basic_string<C>& expected_namespace);

    const std::basic_string<C>&
    encountered_name () const;

    const std::basic_string<C>&
    encountered_namespace () const;

    const std::basic_string<C>&
    expected_name () const;

    const std::basic_string<C>&
    expected_namespace () const;

    virtual const char*
    what () const throw ();
};
```

The `xml_schema::unexpected_element` exception is thrown when an unexpected element is encountered by the DOM-Tree stage. The name and namespace of the encountered element can be obtained using the `encountered_name` and `encountered_namespace` functions respectively. If an element was expected instead of the encountered one, its name and namespace can be obtained using the `expected_name` and `expected_namespace` functions respectively. Otherwise these functions return empty strings.

### 3.3.4 xml\_schema::expected\_attribute

```
struct expected_attribute: virtual exception
{
    expected_attribute (const std::basic_string<C>& name,
                      const std::basic_string<C>& namespace_);

    const std::basic_string<C>&
    name () const;

    const std::basic_string<C>&
    namespace_ () const;

    virtual const char*
    what () const throw ();
};
```

The `xml_schema::expected_attribute` exception is thrown when an expected attribute is not encountered by the DOM-Tree stage. The name and namespace of the expected attribute can be obtained using the `name` and `namespace_` functions respectively.

### 3.3.5 xml\_schema::unexpected\_enumerator

```
struct unexpected_enumerator: virtual exception
{
    unexpected_enumerator (const std::basic_string<C>& enumerator);

    const std::basic_string<C>&
    enumerator () const;

    virtual const char*
    what () const throw ();
};
```

The `xml_schema::unexpected_enumerator` exception is thrown when an unexpected enumerator is encountered by the DOM-Tree stage. The enumerator can be obtained using the `enumerator` functions.

### 3.3.6 xml\_schema::expected\_text\_content

```
struct expected_text_content: virtual exception
{
    virtual const char*
    what () const throw ();
};
```

The `xml_schema::expected_text_content` exception is thrown when a content other than text is encountered and the text content was expected by the DOM-Tree stage.

### 3.3.7 xml\_schema::no\_type\_info

```
struct no_type_info: virtual exception
{
    no_type_info (const std::basic_string<C>& type_name,
                  const std::basic_string<C>& type_namespace);

    const std::basic_string<C>&
    type_name () const;

    const std::basic_string<C>&
    type_namespace () const;

    virtual const char*
    what () const throw ();
};
```

The `xml_schema::no_type_info` exception is thrown when there is no type information associated with a type specified by the `xsi:type` attribute. This exception is thrown by the DOM-Tree stage. The name and namespace of the type in question can be obtained using the `type_name` and `type_namespace` functions respectively. Usually, catching this exception means that you haven't linked the code generated from the schema defining the type in question with your application or this schema has been compiled without the `--generate-polymorphic` option.

### 3.3.8 xml\_schema::not\_derived

```
struct not_derived: virtual exception
{
    not_derived (const std::basic_string<C>& base_type_name,
                  const std::basic_string<C>& base_type_namespace,
                  const std::basic_string<C>& derived_type_name,
                  const std::basic_string<C>& derived_type_namespace);
```

```

const std::basic_string<C>&
base_type_name () const;

const std::basic_string<C>&
base_type_namespace () const;

const std::basic_string<C>&
derived_type_name () const;

const std::basic_string<C>&
derived_type_namespace () const;

virtual const char*
what () const throw ();
};

```

The `xml_schema::not_derived` exception is thrown when a type specified by the `xsi:type` attribute is not derived from the expected base type. This exception is thrown by the DOM-Tree stage. The name and namespace of the expected base type can be obtained using the `base_type_name` and `base_type_namespace` functions respectively. The name and namespace of the offending type can be obtained using the `derived_type_name` and `derived_type_namespace` functions respectively.

### 3.3.9 `xml_schema::no_prefix_mapping`

```

struct no_prefix_mapping: virtual exception
{
    no_prefix_mapping (const std::basic_string<C>& prefix);

    const std::basic_string<C>&
    prefix () const;

    virtual const char*
    what () const throw ();
};

```

The `xml_schema::no_prefix_mapping` exception is thrown during the DOM-Tree stage if a namespace prefix is encountered for which a prefix-namespace mapping hasn't been provided. The namespace prefix in question can be obtained using the `prefix` function.

## 3.4 Reading from a Local File or URI

Using a local file or URI is the simplest way to parse an XML instance. For example:

```
using std::auto_ptr;

auto_ptr<type> r1 (name ("test.xml"));
auto_ptr<type> r2 (name ("http://www.codesynthesis.com/test.xml"));
```

## 3.5 Reading from `std::istream`

When using an `std::istream` instance, you may also pass an optional resource id. This id is used to identify the resource (for example in error messages) as well as to resolve relative paths. For instance:

```
using std::auto_ptr;

{
    std::ifstream ifs ("test.xml");
    auto_ptr<type> r (name (ifs, "test.xml"));
}

{
    std::string str ("..."); // Some XML fragment.
    std::istringstream iss (str);
    auto_ptr<type> r (name (iss));
}
```

## 3.6 Reading from `xercesc::InputSource`

Reading from a `xercesc::InputSource` instance is similar to the `std::istream` case except the resource id is maintained by the `InputSource` object. For instance:

```
xercesc::StdInInputSource is;
std::auto_ptr<type> r (name (is));
```

## 3.7 Reading from DOM

Reading from a `xercesc::DOMDocument` instance allows you to setup a custom XML-DOM stage. Things like DOM parser reuse, schema pre-parsing, and schema caching can be achieved with this approach. For more information on how to obtain DOM representation from an XML instance refer to the Xerces-C++ documentation. In addition, the C++/Tree Mapping FAQ shows how to parse an XML instance to a Xerces-C++ DOM document using the XSD runtime utilities.

The last parsing function is useful when you would like to perform your own XML-to-DOM parsing and associate the resulting DOM document with the object model nodes. If parsing is successful, the automatic `DOMDocument` pointer is reset and the resulting object model assumes ownership of the DOM document passed. For example:

```
xml_schema::dom::auto_ptr<xercesc::DOMDocument> doc = ...

std::auto_ptr<type> r (
    name (doc, xml_schema::flags::keep_dom | xml_schema::flags::own_dom));

// At this point doc is reset to 0.
```

## 4 Serialization

This chapter covers various aspects of serializing a tree-like object model to DOM or XML. In this regard, serialization is complimentary to the reverse process of parsing a DOM or XML instance into an object model which is discussed in Chapter 3, "Parsing". Note that generation of the serialization code is optional and should be explicitly requested with the `--generate-serialization` option. See the XSD Compiler Command Line Manual for more information.

Each global XML Schema element in the form:

```
<xsd:element name="name" type="type"/>
```

is mapped to 8 overloaded C++ functions in the form:

```
// Serialize to std::ostream.
//
void
name (std::ostream&,
      const type&,
      const xml_schema::namespace_fomap& =
          xml_schema::namespace_infomap (),
      const std::basic_string<C>& encoding = "UTF-8",
      xml_schema::flags = 0);

void
name (std::ostream&,
      const type&,
      xml_schema::error_handler&,
      const xml_schema::namespace_infomap& =
          xml_schema::namespace_infomap (),
      const std::basic_string<C>& encoding = "UTF-8",
      xml_schema::flags = 0);

void
name (std::ostream&,
      const type&,
      xercesc::DOMErrorHandler&,
      const xml_schema::namespace_infomap& =
          xml_schema::namespace_infomap (),
      const std::basic_string<C>& encoding = "UTF-8",
```

```

        xml_schema::flags = 0);

// Serialize to XMLFormatTarget.
//
void
name (xercesc::XMLFormatTarget&,
      const type&,
      const xml_schema::namespace_infomap& =
        xml_schema::namespace_infomap (),
      const std::basic_string<C>& encoding = "UTF-8",
      xml_schema::flags = 0);

void
name (xercesc::XMLFormatTarget&,
      const type&,
      xml_schema::error_handler&,
      const xml_schema::namespace_infomap& =
        xml_schema::namespace_infomap (),
      const std::basic_string<C>& encoding = "UTF-8",
      xml_schema::flags = 0);

void
name (xercesc::XMLFormatTarget&,
      const type&,
      xercesc::DOMErrorHandler&,
      const xml_schema::namespace_infomap& =
        xml_schema::namespace_infomap (),
      const std::basic_string<C>& encoding = "UTF-8",
      xml_schema::flags = 0);

// Serialize to DOM.
//
xml_schema::dom::auto_ptr<xercesc::DOMDocument>
name (const type&,
      const xml_schema::namespace_infomap&
        xml_schema::namespace_infomap (),
      xml_schema::flags = 0);

void
name (xercesc::DOMDocument&,
      const type&,
      xml_schema::flags = 0);

```

You can choose between writing XML to `std::ostream` or `xercesc::XMLFormatTarget` and creating a DOM instance in the form of `xercesc::DOMDocument`. Serialization to `ostream` or `XMLFormatTarget` requires a considerably less work while serialization to DOM provides for greater flexibility. Each of these serialization functions is discussed in more detail in the following sections.

## 4.1 Initializing the Xerces-C++ Runtime

Some serialization functions expect you to initialize the Xerces-C++ runtime while others initialize and terminate it as part of their work. The general rule is as follows: if a function has any arguments or return a value that is an instance of a Xerces-C++ type, then this function expects you to initialize the Xerces-C++ runtime. Otherwise, the function initializes and terminates the runtime for you. Note that it is legal to have nested calls to the Xerces-C++ initialize and terminate functions as long as the calls are balanced.

You can instruct serialization functions that initialize and terminate the runtime not to do so by passing the `xml_schema::flags::dont_initialize` flag (see Section 4.3, "Flags").

## 4.2 Namespace Infomap and Character Encoding

When a document being serialized uses XML namespaces, custom prefix-namespace associations can be established. If custom prefix-namespace mapping is not provided then generic prefixes (`p1`, `p2`, etc) are automatically assigned to namespaces as needed. Also, if you would like the resulting instance document to contain the `schemaLocation` or `noNamespaceSchemaLocation` attributes, you will need to provide namespace-schema associations. The `xml_schema::namespace_infomap` class is used to capture this information:

```
struct namespace_info
{
    namespace_info ();
    namespace_info (const std::basic_string<C>& name,
                    const std::basic_string<C>& schema);

    std::basic_string<C> name;
    std::basic_string<C> schema;
};

// Map of namespace prefix to namespace_info.
//
struct namespace_infomap: public std::map<std::basic_string<C>,
                                         namespace_info>
{
};
```

Consider the following associations as an example:

```
xml_schema::namespace_infomap map;

map["t"].name = "http://www.codesynthesis.com/test";
map["t"].schema = "test.xsd";
```

This map, if passed to one of the serialization functions, could result in the following XML fragment:

```
<?xml version="1.0" ?>
<t:name xmlns:t="http://www.codesynthesis.com/test"
        xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
        xsi:schemaLocation="http://www.codesynthesis.com/test test.xsd">
```

As you can see, the serialization function automatically added namespace mapping for the `xsi` prefix. You can change this by providing your own prefix:

```
xml_schema::namespace_infomap map;

map["xsn"].name = "http://www.w3.org/2001/XMLSchema-instance";

map["t"].name = "http://www.codesynthesis.com/test";
map["t"].schema = "test.xsd";
```

This could result in the following XML fragment:

```
<?xml version="1.0" ?>
<t:name xmlns:t="http://www.codesynthesis.com/test"
        xmlns:xsn="http://www.w3.org/2001/XMLSchema-instance"
        xsn:schemaLocation="http://www.codesynthesis.com/test test.xsd">
```

To specify the location of a schema without a namespace you can use an empty prefix as in the example below:

```
xml_schema::namespace_infomap map;

map[""].schema = "test.xsd";
```

This would result in the following XML fragment:

```
<?xml version="1.0" ?>
<name xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:noNamespaceSchemaLocation="test.xsd">
```

To make a particular namespace default you can use an empty prefix, for example:

```
xml_schema::namespace_infomap map;

map[""].name = "http://www.codesynthesis.com/test";
map[""].schema = "test.xsd";
```

This could result in the following XML fragment:

```
<?xml version="1.0" ?>
<name xmlns="http://www.codesynthesis.com/test"
      xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:schemaLocation="http://www.codesynthesis.com/test test.xsd">
```

Another bit of information that you can pass to the serialization functions is the character encoding method that you would like to use. Common values for this argument are "USASCII", "ISO8859-1", "UTF-8", "UTF-16BE", "UTF-16LE", "UCS-4BE", and "UCS-4LE". The default encoding is "UTF-8". For more information on encoding methods see the "Character Encoding" article from Wikipedia.

## 4.3 Flags

Serialization flags are the last argument of every serialization function. They allow you to fine-tune the process of serialization. The flags argument is optional.

The following flags are recognized by the serialization functions:

```
xml_schema::flags::dont_initialize
    Do not initialize the Xerces-C++ runtime.
xml_schema::flags::dont_pretty_print
    Do not add extra spaces or new lines that make the resulting XML slightly bigger but easier
    to read.
xml_schema::flags::no_xml_declaration
    Do not write XML declaration (<?xml ... ?>).
```

You can pass several flags by combining them using the bit-wise OR operator. For example:

```
std::auto_ptr<type> r = ...
std::ofstream ofs ("test.xml");
xml_schema::namespace_infomap map;
name (ofs,
      *r,
      map,
      "UTF-8",
      xml_schema::flags::no_xml_declaration |
      xml_schema::flags::dont_pretty_print);
```

For more information on the Xerces-C++ runtime initialization refer to Section 4.1, "Initializing the Xerces-C++ Runtime".

## 4.4 Error Handling

As with the parsing functions (see Section 3.3, "Error Handling"), to better understand error handling and reporting strategies employed by the serialization functions, it is useful to know that the transformation of a statically-typed tree to an XML instance document happens in two stages. The first stage, performed by the generated code, consist of building a DOM instance from the statically-typed tree . For short, we will call this stage the Tree-DOM stage. The second stage, performed by Xerces-C++, consists of serializing the DOM instance into the XML document. We will call this stage the DOM-XML stage.

All serialization functions except the two that serialize into a DOM instance come in overloaded triples. The first function in such a triple reports error conditions exclusively by throwing exceptions. It accumulates all the serialization errors of the DOM-XML stage and throws them in a single instance of the `xml_schema::serialization` exception (described below). The second and the third functions in the triple use callback interfaces to report serialization errors and warnings. The two callback interfaces are `xml_schema::error_handler` and `xercesc::DOMErrorHandler`. The `xml_schema::error_handler` interface is described in Section 3.3, "Error Handling". For more information on the `xercesc::DOMErrorHandler` interface refer to the Xerces-C++ documentation.

The Tree-DOM stage reports error conditions exclusively by throwing exceptions. Individual exceptions thrown by the serialization functions are described in the following sub-sections.

### 4.4.1 `xml_schema::serialization`

```
struct serialization: virtual exception
{
    serialization ();
    serialization (const diagnostics&);

    const diagnostics&
    diagnostics () const;

    virtual const char*
    what () const throw ();
};
```

The `xml_schema::diagnostics` class is described in Section 3.3.1, "xml\_schema::parsing". The `xml_schema::serialization` exception is thrown if there were serialization errors reported during the DOM-XML stage. If no callback interface was provided to the serialization function, the exception contains a list of errors and warnings accessible using the `diagnostics` function.

### 4.4.2 `xml_schema::unexpected_element`

The `xml_schema::unexpected_element` exception is described in Section 3.3.3, "`xml_schema::unexpected_element`". It is thrown by the serialization functions during the Tree-DOM stage if the root element name of the provided DOM instance does not match with the name of the element this serialization function is for.

### 4.4.3 `xml_schema::no_type_info`

The `xml_schema::no_type_info` exception is described in Section 3.3.7, "`xml_schema::no_type_info`". It is thrown by the serialization functions during the Tree-DOM stage when there is no type information associated with a dynamic type of an element. Usually, catching this exception means that you haven't linked the code generated from the schema defining the type in question with your application or this schema has been compiled without the `--generate-polymorphic` option.

## 4.5 Serializing to `std::ostream`

In order to serialize to `std::ostream` you will need an object model, an output stream and, optionally, a namespace infomap. For instance:

```
// Obtain the object model.
//
std::auto_ptr<type> r = ...

// Prepare namespace mapping and schema location information.
//
xml_schema::namespace_infomap map;

map["t"].name = "http://www.codesynthesis.com/test";
map["t"].schema = "test.xsd";

// Write it out.
//
name (std::cout, *r, map);
```

Note that the output stream is treated as a binary stream. This becomes important when you use a character encoding that is wider than 8-bit `char`, for instance UTF-16 or UCS-4. For example, things will most likely break if you try to serialize to `std::ostringstream` with UTF-16 or UCS-4 as an encoding. This is due to the special value, `'\0'`, that will most likely occur as part of such serialization and it won't have the special meaning assumed by `std::ostringstream`.

## 4.6 Serializing to xercesc::XMLFormatTarget

Serializing to an xercesc::XMLFormatTarget instance is similar the std::ostream case. For instance:

```
using std::auto_ptr;

// Obtain the object model.
//
auto_ptr<type> r = ...

// Prepare namespace mapping and schema location information.
//
xml_schema::namespace_infomap map;

map["t"].name = "http://www.codesynthesis.com/test";
map["t"].schema = "test.xsd";

using namespace xercesc;

XMLPlatformUtils::Initialize ();

{
    // Choose a target.
    //
    auto_ptr<XMLFormatTarget> ft;

    if (argc != 2)
    {
        ft = auto_ptr<XMLFormatTarget> (new StdOutFormatTarget ());
    }
    else
    {
        ft = auto_ptr<XMLFormatTarget> (
            new LocalFileFormatTarget (argv[1]));
    }

    // Write it out.
    //
    name (*ft, *r, map);
}

XMLPlatformUtils::Terminate ();
```

Note that we had to initialize the Xerces-C++ runtime before we could call this serialization function.

## 4.7 Serializing to DOM

The mapping provides two overloaded functions that implement serialization to a DOM instance. The first creates a DOM instance for you and the second serializes to an existing DOM instance. While serializing to a new DOM instance is similar to serializing to `std::ostream` or `xercesc::XMLFormatTarget`, serializing to an existing DOM instance requires quite a bit of work from your side. You will need to set all the custom namespace mapping attributes as well as the `schemaLocation` and/or `noNamespaceSchemaLocation` attributes. The following listing should give you an idea about what needs to be done:

```
// Obtain the object model.
//
std::auto_ptr<type> r = ...

using namespace xercesc;

XMLPlatformUtils::Initialize ();

{
    // Create a DOM instance. Set custom namespace mapping and schema
    // location attributes.
    //
    DOMDocument& doc = ...

    // Serialize to DOM.
    //
    name (doc, *r);

    // Serialize the DOM document to XML.
    //
    ...
}

XMLPlatformUtils::Terminate ();
```

For more information on how to create and serialize a DOM instance refer to the Xerces-C++ documentation. In addition, the C++/Tree Mapping FAQ shows how to implement these operations using the XSD runtime utilities.

## 5 Additional Functionality

The C++/Tree mapping provides a number of optional features that can be useful in certain situations. They are described in the following sections.

## 5.1 DOM Association

Normally, after parsing is complete, the DOM document which was used to extract the data is discarded. However, the parsing functions can be instructed to preserve the DOM document and create an association between the DOM nodes and object model nodes. When there is an association between the DOM and object model nodes, you can obtain the corresponding DOM element or attribute node from an object model node as well as perform the reverse transition: obtain the corresponding object model from a DOM element or attribute node.

Maintaining DOM association is normally useful when the application needs access to XML constructs that are not preserved in the object model, for example, text in the mixed content model. Another useful aspect of DOM association is the ability of the application to navigate the document tree using the generic DOM interface (for example, with the help of an XPath processor) and then move back to the statically-typed object model. Note also that while you can change the underlying DOM document, these changes are not reflected in the object model and will be ignored during serialization. If you need to not only access but also modify some aspects of XML that are not preserved in the object model, then type customization with custom parsing constructs and serialization operators should be used instead.

To request DOM association you will need to pass the `xml_schema::flags::keep_dom` flag to one of the parsing functions (see Section 3.2, "Flags and Properties" for more information). In this case the DOM document is retained and will be released when the object model is deleted. Note that since DOM nodes "out-live" the parsing function call, you need to initialize the Xerces-C++ runtime before calling one of the parsing functions with the `keep_dom` flag and terminate it after the object model is destroyed (see Section 3.1, "Initializing the Xerces-C++ Runtime"). The DOM association is also maintained in complete copies of the object model (that is, the DOM document is cloned and associations are reestablished).

To obtain the corresponding DOM node from an object model node you will need to call the `_node` accessor function which returns a pointer to `DOMNode`. You can then query this DOM node's type and cast it to either `DOMAttr*` or `DOMElement*`. To obtain the corresponding object model node from a DOM node, the DOM user data API is used. The `xml_schema::dom::tree_node_key` variable contains the key for object model nodes. The following schema and code fragment show how to navigate from DOM to object model nodes and in the opposite direction:

```
<complexType name="object">
  <sequence>
    <element name="a" type="string"/>
  </sequence>
</complexType>

<element name="root" type="object"/>
```

```

using namespace xercesc;

XMLPlatformUtils::Initialize ();

{
    // Parse XML to object model.
    //
    std::auto_ptr<type> r = root (
        "root.xml",
        xml_schema::flags::keep_dom |
        xml_schema::flags::dont_initialize);

    DOMNode* n = root->_node ();
    assert (n->getNodeType () != DOMNode::ELEMENT_NODE);
    DOMElement* re = static_cast<DOMElement*> (n);

    // Get the 'a' element. Note that it is not necessarily the
    // first child node of 'root' since there could be whitespace
    // nodes before it.
    //
    DOMElement* ae;

    for (n = re->getFirstChild (); n != 0; n = n->getNextSibling ())
    {
        if (n->getNodeType () == DOMNode::ELEMENT_NODE)
        {
            ae = static_cast<DOMElement*> (n);
            break;
        }
    }

    // Get from the 'a' DOM element to xml_schema::string object model
    // node.
    //
    xml_schema::type& t (
        *reinterpret_cast<xml_schema::type*> (
            ae->getUserData (xml_schema::dom::tree_node_key)));

    xml_schema::string& a (dynamic_cast<xml_schema::string&> (t));
}

XMLPlatformUtils::Terminate ();

```

The 'mixed' example which can be found in the XSD distribution shows how to handle the mixed content using DOM association.

## 5.2 Binary Serialization

Besides reading from and writing to XML, the C++/Tree mapping also allows you to save the object model to and load it from a number of predefined as well as custom data representation formats. The predefined binary formats are CDR (Common Data Representation) and XDR (eXternal Data Representation). A custom format can easily be supported by providing insertion and extraction operators for basic types.

Binary serialization saves only the data without any meta information or markup. As a result, saving to and loading from a binary representation can be an order of magnitude faster than parsing and serializing the same data in XML. Furthermore, the resulting representation is normally several times smaller than the equivalent XML representation. These properties make binary serialization ideal for internal data exchange and storage. A typical application that uses this facility stores the data and communicates within the system using a binary format and reads/writes the data in XML when communicating with the outside world.

In order to request the generation of insertion operators and extraction constructors for a specific predefined or custom data representation stream, you will need to use the `--generate-insertion` and `--generate-extraction` compiler options. See the XSD Compiler Command Line Manual for more information.

Once the insertion operators and extraction constructors are generated, you can use the `xml_schema::istream` and `xml_schema::ostream` wrapper stream templates to save the object model to and load it from a specific format. The following code fragment shows how to do this using ACE (Adaptive Communication Environment) CDR streams as an example:

```
<complexType name="object">
  <sequence>
    <element name="a" type="string"/>
    <element name="b" type="int"/>
  </sequence>
</complexType>

<element name="root" type="object"/>

// Parse XML to object model.
//
std::auto_ptr<type> r = root ("root.xml");

// Save to a CDR stream.
//
ACE_OutputCDR ace_ocdr;
xml_schema::ostream<ACE_OutputCDR> ocdr (ace_ocdr);

ocdr << *r;

// Load from a CDR stream.
```

```
//
ACE_InputCDR ace_icdr (buf, size);
xml_schema::istream<ACE_InputCDR> icdr (ace_icdr);

std::auto_ptr<object> copy (new object (icdr));

// Serialize to XML.
//
root (std::cout, *copy);
```

The XSD distribution contains a number of examples that show how to save the object model to and load it from CDR, XDR, and a custom format.

## Appendix A — Default and Fixed Values

The following table summarizes the effect of default and fixed values (specified with the `default` and `fixed` attributes, respectively) on attribute and element values. The `default` and `fixed` attributes are mutually exclusive. It is also worthwhile to note that the fixed value semantics is a superset of the default value semantics.

		default		fixed	
element	not present	optional	required	optional	required
		not present	invalid instance	not present	invalid instance
	empty	default value is used		fixed value is used	
	value	value is used		value is used provided it's the same as fixed	
attribute	not present	optional	required	optional	required
		default value is used	invalid schema	fixed value is used	invalid instance
	empty	empty value is used		empty value is used provided it's the same as fixed	
	value	value is used		value is used provided it's the same as fixed	